



WR-137 Waveguide Shim, CPR-137F Flange, 2 mm Brass

Waveguide Accessories Technical Data Sheet

PEW137FS2

Features

- WR-137 Waveguide Shim
- CPR-137F Flange Configuration
- Frequency Range: 5.38 GHz to 8.17 GHz
- 2 mm Thick Brass Construction

Description

PEW137FS2 is a WR-137 waveguide shim with operating frequency range from 5.38 GHz to 8.17 GHz. This waveguide shim is fabricated with 2 mm thick brass by high precision manufacturing process. PEW137FS2 can be used to bridge gaps between WR-137 waveguide components with UG-Cover Square flanges. Pasternack offers wide selection of waveguide components with high performance available in stock and same-day shipping to customers worldwide.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	5.38		8.17	GHz

Mechanical Specifications

Body Material	Brass
Body Finish	Passivation
Length	0.079 in [2.01 mm]
Width	2.689 in [68.3 mm]
Height	1.937 in [49.2 mm]
Weight	0.132 lbs [59.87 g]

Compliance Certifications (see [product page](#) for current document)

WR-137 Waveguide Shim, CPR-137F Flange, 2 mm Brass from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-137 Waveguide Shim, CPR-137F Flange, 2 mm Brass PEW137FS2](#)



URL: <https://www.pasternack.com/wr-137-waveguide-shim-2-mm-brass-cpr-137f-pew137fs2-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PEW137FS2 CAD Drawing

WR-137 Waveguide Shim, CPR-137F Flange, 2 mm Brass

REVISIONS		
REV.	DESCRIPTION	DATE
A	INITIAL RELEASE	4/13/2022
		APPROVED S. PONG



UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:

.X = ±.2 [5.08] FRACTIONS ± 1/32
 .XX = ±.02 [.51] ANGLES ± 1°
 .XXX = ±.005 [.13] CABLE LENGTH (L), TOLERANCES:
 L ≤ 12 [305] = +1 [25] / -0
 12 [305] < L ≤ 60 [1524] = +2 [51] / -0
 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0
 120 [3048] < L ≤ 300 [7620] = +6 [152] / -0
 300 [7620] < L = +5% / -0

ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.

PE **PASTERNAK**
 an INFINIT[®] brand

Pasternack Enterprises, Inc.
 P. O. Box 16759, Irvine, CA 92623.
 Phone: 1.949.261.1920 | 1.866.727.8376
 Fax: 1.949.261.7451
 Website: www.pasternack.com
 E-mail: sales@pasternack.com

SCALE N/A

SHEET 1 OF 1

THIRD-ANGLE PROJECTION

THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF PASTERNAK CORPORATION ALL RIGHTS RESERVED.

ITEM NO. PEW137FS2

SIZE A

CAGE CODE 53919

DRAWN BY K.DANG

REV A