



			1	
	Part Number:		DRAWN	3/23/2017
	CM20	2600 1	CJ	
	SW390	7009-1	CHECKED	10/5/2017
			P.D.	
	Description:		APPROVED	10/5/2017
Waterproof Dyr	namic Speaker	C.E.	10/5/2017	

This document contains data proprietary to DB Unlimited. Any use or reproduction, in any form, without prior written permission of DB Unlimited is prohibited. All terms and conditions can be found at www.dbunlimitedco.com


Top View



Side View



Bottom View



Items	Specifications	Conditions					
Sound Pressure Level	95	dB (@ 10cm), Avg.					
Resonant Frequency	600	Hz	REVISION HISTORY				
Frequency Range	600 ~ 20,000	Hz	REV	DESCRIPTION	DATE	APPROVED	
Nominal Power	1.5	W		Released from Engineering	10/5/2017	C.E.	
Max. Power	2	W	1	Added polarity marking	10/25/2017	C.E.	
Impedance	8	Ω	2	Update markings	2/28/2018	C.E.	
Cone Material	Mylar		NOTES				
Mount Type	Flush Mount		All dimensions are in mm unless otherwise noted				
IP Rating	IP67		2) All tolerances are ± 0.2 mm unless otherwise noted				
Storage Temperature	-20 ~ +55	°C	3) All parts meet RoHS				
Operating Temperature	-20 ~ +55	°C	4) Subject to change or redrawn without notice				