

## Surge Suppressor- State of the art protection for every application

MODEL NUMBER: **S6-DLX**



### Highlights

- 6 outlets/6 ft. cord
- 1050 joule rating
- Modem/fax surge protection
- \$15,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

### Package Includes

- S6-DLX Surge Suppressor
- Telephone cord
- Child Safety Covers
- Color-coded cord identifiers
- Warranty information with instruction manual

### Description

The S6-DLX Surge Suppressor from Tripp Lite has 6 outlets and a 6-ft. cord with a space-saving right-angle plug. The unit has 1,050 joules of surge energy absorption to handle the strongest surges. Built-in RJ11 jacks prevent surges from damaging your modem/fax/phone equipment. A telephone cord is also included. Diagnostic LEDs alert the user to potential power problems. \$15,000 Ultimate Lifetime Insurance (USA & Canada Only). No warranty cards required for coverage! The Super 6 Deluxe comes with child safety covers and color-coded cord identifiers.

### Features

- 6 outlets with child safety covers
- 6-ft. cord with space-saving right-angle plug
- Built-in RJ11 jacks prevent surges from damaging your modem / fax / phone equipment; 6-ft. telephone cord included
- \$15,000 Ultimate Lifetime Insurance (USA & Canada Only) covers connected equipment - No warranty cards required for coverage!
- Surge energy absorption: 1,050 joules; 42,500 amps
- 15 amp circuit breaker
- 2 diagnostic LEDs indicate AC present & line fault
- EMI/RFI noise filtering
- Keyhole supports for wall mounting
- Color-coded cord identifiers
- Lifetime product warranty

## Specifications

INPUT	
Nominal Input Voltage(s) Supported	100V AC

Recommended Electrical Service	120V (110-125V)
Voltage Compatibility (VAC)	120
Input Plug Type	NEMA 5-15P
Input Cord Length (ft.)	6
Right-Angle Plug	Yes
Input Cord Length (m)	1.83
Integrated Cord Clip	No
<b>OUTPUT</b>	
Frequency Compatibility	50 / 60 Hz
Output Receptacles	(6) 5-15R
Circuit Breaker (amps)	15
Transformer Accommodation	(2) Yes
<b>USER INTERFACE, ALERTS &amp; CONTROLS</b>	
Diagnostic LED(s)	Yes
Switches	Two position on/off power switch
Diagnostic LED Details	PROTECTION PRESENT, LINE OK
<b>SURGE / NOISE SUPPRESSION</b>	
AC Suppression Joule Rating	1050
AC Suppression Response Time	< 1 ns
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
AC Suppression Surge Current Rating	42,500 amps
UL1449 Let Through Rating	330V - UL Verified
EMI / RFI Filtering	Yes
Immunity	Conforms to IEE 587 / ANSI C62.41
Automatic Shut-Off	No
<b>DATALINE SURGE SUPPRESSION</b>	
Telephone/DSL Protection Details	1 line
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
Telephone/DSL Protection	Yes
<b>PHYSICAL</b>	
Color	Light Gray

Material of Construction	Plastic
Power Cord Color	Light Gray
Housing Color	Light Gray
Mounting Holes or Slots	Yes
Receptacle Color	Light gray
Unit Dimensions (hwd / in.)	1.250 x 3.250 x 8.250
Unit Dimensions (hwd / cm)	3.2 x 8.3 x 21
<b>FEATURES &amp; SPECIFICATIONS</b>	
Antimicrobial	No
Rotatable Outlets	No
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$15,000 <a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a>