

International Rectifier

PD - 95296

IRF7317PbF

HEXFET® Power MOSFET


- Generation V Technology
- Ultra Low On-Resistance
- Dual N and P Channel MOSFET
- Surface Mount
- Fully Avalanche Rated
- Lead-Free

Description

Fifth Generation HEXFETs from International Rectifier utilize advanced processing techniques to achieve extremely low on-resistance per silicon area. This benefit, combined with the fast switching speed and ruggedized device design that HEXFET Power MOSFETs are well known for, provides the designer with an extremely efficient and reliable device for use in a wide variety of applications.

The SO-8 has been modified through a customized leadframe for enhanced thermal characteristics and multiple-die capability making it ideal in a variety of power applications. With these improvements, multiple devices can be used in an application with dramatically reduced board space. The package is designed for vapor phase, infra red, or wave soldering techniques.

	N-Ch	P-Ch
V_{DSS}	20V	-20V
$R_{DS(on)}$	0.029Ω	0.058Ω



Absolute Maximum Ratings ($T_A = 25^\circ\text{C}$ Unless Otherwise Noted)

	Symbol	Maximum		Units
		N-Channel	P-Channel	
Drain-Source Voltage	V_{DS}	20	-20	
Gate-Source Voltage	V_{GS}	± 12		
Continuous Drain Current ^⑤	$T_A = 25^\circ\text{C}$	6.6	-5.3	A
	$T_A = 70^\circ\text{C}$	5.3	-4.3	
Pulsed Drain Current	I_{DM}	26	-21	
Continuous Source Current (Diode Conduction)	I_S	2.5	-2.5	
Maximum Power Dissipation ^⑤	$T_A = 25^\circ\text{C}$	2.0		W
	$T_A = 70^\circ\text{C}$	1.3		
Single Pulse Avalanche Energy	E_{AS}	100	150	mJ
Avalanche Current	I_{AR}	4.1	-2.9	A
Repetitive Avalanche Energy	E_{AR}	0.20		mJ
Peak Diode Recovery dv/dt ^②	dv/dt	5.0	-5.0	V/ ns
Junction and Storage Temperature Range	T_J, T_{STG}	-55 to + 150 °C		

Thermal Resistance Ratings

Parameter	Symbol	Limit	Units
Maximum Junction-to-Ambient ^⑥	$R_{\theta JA}$	62.5	°C/W

IRF7317PbF

International
Rectifier

Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

	Parameter		Min.	Typ.	Max.	Units	Conditions
$V_{(\text{BR})\text{DSS}}$	Drain-to-Source Breakdown Voltage	N-Ch	20	—	—	V	$V_{GS} = 0\text{V}, I_D = 250\mu\text{A}$
		P-Ch	-20	—	—		$V_{GS} = 0\text{V}, I_D = -250\mu\text{A}$
$\Delta V_{(\text{BR})\text{DSS}}/\Delta T_J$	Breakdown Voltage Temp. Coefficient	N-Ch	—	0.027	—	V/ $^\circ\text{C}$	Reference to 25°C , $I_D = 1\text{mA}$
		P-Ch	—	0.031	—		Reference to 25°C , $I_D = -1\text{mA}$
$R_{DS(\text{ON})}$	Static Drain-to-Source On-Resistance	N-Ch	—	0.023	0.029	Ω	$V_{GS} = 4.5\text{V}, I_D = 6.0\text{A}$ ④
		N-Ch	—	0.030	0.046		$V_{GS} = 2.7\text{V}, I_D = 5.2\text{A}$ ④
		P-Ch	—	0.049	0.058		$V_{GS} = -4.5\text{V}, I_D = -2.9\text{A}$ ④
		P-Ch	—	0.082	0.098		$V_{GS} = -2.7\text{V}, I_D = -1.5\text{A}$ ④
$V_{GS(\text{th})}$	Gate Threshold Voltage	N-Ch	0.7	—	—	V	$V_{DS} = V_{GS}, I_D = 250\mu\text{A}$
		P-Ch	-0.7	—	—		$V_{DS} = V_{GS}, I_D = -250\mu\text{A}$
g_{fs}	Forward Transconductance	N-Ch	—	20	—	S	$V_{DS} = 10\text{V}, I_D = 6.0\text{A}$ ④
		P-Ch	—	5.9	—		$V_{DS} = -10\text{V}, I_D = -1.5\text{A}$ ④
I_{DSS}	Drain-to-Source Leakage Current	N-Ch	—	—	1.0	μA	$V_{DS} = 16\text{V}, V_{GS} = 0\text{V}$
		P-Ch	—	—	-1.0		$V_{DS} = -16\text{V}, V_{GS} = 0\text{V}$
		N-Ch	—	—	5.0		$V_{DS} = 16\text{V}, V_{GS} = 0\text{V}, T_J = 55^\circ\text{C}$
		P-Ch	—	—	-25		$V_{DS} = -16\text{V}, V_{GS} = 0\text{V}, T_J = 55^\circ\text{C}$
I_{GSS}	Gate-to-Source Forward Leakage	N-P	—	—	± 100	nA	$V_{GS} = \pm 12\text{V}$
Q_g	Total Gate Charge	N-Ch	—	18	27	nC	N-Channel $I_D = 6.0\text{A}, V_{DS} = 10\text{V}, V_{GS} = 4.5\text{V}$ ④
		P-Ch	—	19	29		P-Channel $I_D = -2.9\text{A}, V_{DS} = -16\text{V}, V_{GS} = -4.5\text{V}$
Q_{gs}	Gate-to-Source Charge	N-Ch	—	2.2	3.3		
		P-Ch	—	4.0	6.1		
Q_{gd}	Gate-to-Drain ("Miller") Charge	N-Ch	—	6.2	9.3		
		P-Ch	—	7.7	12		
$t_{d(on)}$	Turn-On Delay Time	N-Ch	—	8.1	12	ns	N-Channel $V_{DD} = 10\text{V}, I_D = 1.0\text{A}, R_G = 6.0\Omega, R_D = 10\Omega$ ④
		P-Ch	—	15	22		
t_r	Rise Time	N-Ch	—	17	25		
		P-Ch	—	40	60		
$t_{d(off)}$	Turn-Off Delay Time	N-Ch	—	38	57	ns	P-Channel $V_{DD} = -10\text{V}, I_D = -2.9\text{A}, R_G = 6.0\Omega, R_D = 3.4\Omega$ ④
		P-Ch	—	42	63		
t_f	Fall Time	N-Ch	—	31	47		
		P-Ch	—	49	73		
C_{iss}	Input Capacitance	N-Ch	—	900	—	pF	N-Channel $V_{GS} = 0\text{V}, V_{DS} = 15\text{V}, f = 1.0\text{MHz}$
		P-Ch	—	780	—		
C_{oss}	Output Capacitance	N-Ch	—	430	—		P-Channel $V_{GS} = 0\text{V}, V_{DS} = -15\text{V}, f = 1.0\text{MHz}$
		P-Ch	—	470	—		
C_{rss}	Reverse Transfer Capacitance	N-Ch	—	200	—		
		P-Ch	—	240	—		

Source-Drain Ratings and Characteristics

	Parameter		Min.	Typ.	Max.	Units	Conditions
I_S	Continuous Source Current (Body Diode)	N-Ch	—	—	2.5	A	
		P-Ch	—	—	-2.5		
I_{SM}	Pulsed Source Current (Body Diode) ④	N-Ch	—	—	26		
		P-Ch	—	—	-21		
V_{SD}	Diode Forward Voltage	N-Ch	—	0.72	1.0	V	$T_J = 25^\circ\text{C}, I_S = 1.7\text{A}, V_{GS} = 0\text{V}$ ③
		P-Ch	—	-0.78	-1.0		$T_J = 25^\circ\text{C}, I_S = -2.9\text{A}, V_{GS} = 0\text{V}$ ③
t_{rr}	Reverse Recovery Time	N-Ch	—	52	77	ns	N-Channel $T_J = 25^\circ\text{C}, I_F = 1.7\text{A}, di/dt = 100\text{A}/\mu\text{s}$
		P-Ch	—	47	71		
Q_{rr}	Reverse Recovery Charge	N-Ch	—	58	86	nC	P-Channel $T_J = 25^\circ\text{C}, I_F = -2.9\text{A}, di/dt = 100\text{A}/\mu\text{s}$ ④
		P-Ch	—	49	73		

Notes:

- ① Repetitive rating; pulse width limited by max. junction temperature. (See fig. 22)
- ② N-Channel $I_{SD} \leq 4.1\text{A}$, $di/dt \leq 92\text{A}/\mu\text{s}$, $V_{DD} \leq V_{(\text{BR})\text{DSS}}$, $T_J \leq 150^\circ\text{C}$
P-Channel $I_{SD} \leq -2.9\text{A}$, $di/dt \leq -77\text{A}/\mu\text{s}$, $V_{DD} \leq V_{(\text{BR})\text{DSS}}$, $T_J \leq 150^\circ\text{C}$
- ③ N-Channel Starting $T_J = 25^\circ\text{C}$, $L = 12\text{mH}$ $R_G = 25\Omega$, $I_{AS} = 4.1\text{A}$. (See Figure 12)
P-Channel Starting $T_J = 25^\circ\text{C}$, $L = 35\text{mH}$ $R_G = 25\Omega$, $I_{AS} = -2.9\text{A}$.
- ④ Pulse width $\leq 300\mu\text{s}$; duty cycle $\leq 2\%$.
- ⑤ Surface mounted on FR-4 board, $t \leq 10\text{sec}$.

International
 Rectifier

N-Channel

IRF7317PbF




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. Typical Transfer Characteristics




Fig 4. Typical Source-Drain Diode Forward Voltage

IRF7317PbF

N-Channel

International
Rectifier




Fig 5. Normalized On-Resistance Vs. Temperature




Fig 6. Typical On-Resistance Vs. Drain Current




Fig 7. Typical On-Resistance Vs. Gate Voltage




Fig 8. Maximum Avalanche Energy Vs. Drain Current




Fig 9. Typical Capacitance Vs.
Drain-to-Source Voltage




Fig 10. Typical Gate Charge Vs.
Gate-to-Source Voltage




Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient

IRF7317PbF

P-Channel

International
Rectifier




Fig 12. Typical Output Characteristics




Fig 13. Typical Output Characteristics




Fig 14. Typical Transfer Characteristics




Fig 15. Typical Source-Drain Diode Forward Voltage




Fig 16. Normalized On-Resistance Vs. Temperature




Fig 17. Typical On-Resistance Vs. Drain Current




Fig 18. Typical On-Resistance Vs. Gate Voltage




Fig 19. Maximum Avalanche Energy Vs. Drain Current

IRF7317PbF

P-Channel

International
Rectifier




Fig 20. Typical Capacitance Vs.
Drain-to-Source Voltage




Fig 21. Typical Gate Charge Vs.
Gate-to-Source Voltage







Fig 22. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient

SO-8 Package Outline

Dimensions are shown in millimeters (inches)




DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	.0532	.0688	1.35	1.75
A1	.004	.0098	0.10	0.25
b	.013	.020	0.33	0.51
c	.0075	.0098	0.19	0.25
D	.189	.1968	4.80	5.00
E	.1497	.1574	3.80	4.00
e	.050	BASIC	1.27	BASIC
e1	.025	BASIC	0.635	BASIC
H	.2284	.2440	5.80	6.20
K	.0099	.0196	0.25	0.50
L	.016	.050	0.40	1.27
y	0°	8°	0°	8°



- NOTES:
1. DIMENSIONING & TOLERANCING PER ASME Y14.5M-1994.
 2. CONTROLLING DIMENSION: MILLIMETER
 3. DIMENSIONS ARE SHOWN IN MILLIMETERS (INCHES).
 4. OUTLINE CONFORMS TO JEDEC OUTLINE MS-012AA.
 5. DIMENSION DOES NOT INCLUDE MOLD PROTRUSIONS. MOLD PROTRUSIONS NOT TO EXCEED 0.15 (.006).
 6. DIMENSION DOES NOT INCLUDE MOLD PROTRUSIONS. MOLD PROTRUSIONS NOT TO EXCEED 0.25 (.010).
 7. DIMENSION IS THE LENGTH OF LEAD FOR SOLDERING TO A SUBSTRATE.

SO-8 Part Marking Information (Lead-Free)

EXAMPLE: THIS IS AN IRF7101 (MOSFET)




IRF7317PbF

International
IR Rectifier


SO-8 Tape and Reel

Dimensions are shown in millimeters (inches)



NOTES:

1. CONTROLLING DIMENSION : MILLIMETER.
2. ALL DIMENSIONS ARE SHOWN IN MILLIMETERS(INCHES).
3. OUTLINE CONFORMS TO EIA-481 & EIA-541.



NOTES:

1. CONTROLLING DIMENSION : MILLIMETER.
2. OUTLINE CONFORMS TO EIA-481 & EIA-541.

Data and specifications subject to change without notice.
This product has been designed and qualified for the Consumer market.
Qualification Standards can be found on IR's Web site.

International
IR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7903
Visit us at www.irf.com for sales contact information.05/04

IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

For further information on the product, technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies office (www.infineon.com).

WARNINGS

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.