THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT INVENTORY NUMBERING SYSTEM

HST 0.4 - 3 _ 0 2 (H) (G) Y = INTERNAL CODE (A)

- COLOR: NONE = BLACK, 2 = RED
- PACKAGE QTY: 1 = 1 PC., 2 = 2 PCS., 3 = 3 PCS., 5 = 5 PCS., X = 10 PCS., 0 = 25 PCS.
- LENGTH: 3 = 3" (76.2mm), 6 = 6" (152mm), 9 = 9" (229mm), 12 = 12" (305mm), 48 = 48" (1219mm)
- EXPANDED INSIDE DIAMETER TUBING
- THICK WALL, ADHESIVE LINED HEAT SHRINK TUBING.

PANDUIT PART NUMBER	Min. Exp. I.D In.(mm)	Max. Rec. I.D In.(mm)	NOMINAL REC WALL THICKNESS In.(mm)	
HST0.4-_-__(Y)	0.400 (10.2)	0.160 (4.1)	0.08 (2.0)	(D)
HST0.8-_-__(Y)	0.750 (19.1)	0.220 (5.6)	0.09 (2.3)	(D)
HST1.1-_-__(Y)	1.100 (27.9)	0.375 (9.5)	0.12 (3.0)	
HST1.5-_-__(Y)	1.500 (38.1)	0.500 (12.7)	0.16 (4.1)	(D)
HST2.0-_-__(Y)	2.000 (50.8)	0.666 (16.9)	0.16 (4.1)	(D)
HST2.7-_-__(Y)	2.700 (68.6)	.870 (22.1)	0.16 (4.1)	(C)
HST3.0-_-____	3.000 (76.2)	1.000 (25.4)	0.16 (4.1)	(F)
HST3.5-_-__(Y)	3.500 (88.9)	1.200 (30.5)	0.16 (4.1)	(C)

(B) NOTES:

1. APPROXIMATE SHRINK RATIO: 3:1(EXPANDED:RECOVERED ID)
2. SHRINK RATIOS ARE APPROXIMATIONS; PLEASE REFER TO TABLE 1 FOR THE EXACT MIMIMUM EXPANDED AND MAXIMUM RECOVERED I.D 'S.
3. MATERIAL: CROSSLINKED POLYOLEFIN
4. COLOR: BLACK AND RED
5. "ALL WARRANTIES, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE EXCLUDED. (USER IS RESPONSIBLE TO DETERMINE SUITABILITY OF PRODUCT FOR INTENDED USE."

(I) 6. ALL PARTS ARE RoHS COMPLIANT

REV	DATE	BY	CHK	DESCRIPTION	ECN - R	CUST	SUP	
--	----	--	--	I ADDED NOTE #6 H CHANGE Y: (RoHs COMPLIANT) TO INTERNAL CODE G CHANGED (MM TOL.)FROM 10.1 TO 10.2 ON PART HST0.4 F PUT HST3.0 BACK ON DRAWING		--	--	--	--
3	2/25/11	LEF			GB0239KM 3	RAMI			
--	----	--	--	(A) ADDED Y:ROHS (B) CHANGED NOTE 1 (C) ADDED LINES HST2.7 & 3.5 (D) DIM. CHANGES (E) REMOVED HST 3.0 LINE		--	--	--	--
2	10/12/10	LEF			GB0239KM 2	RAMI			

DIMENSIONS IN BRACKETS ARE METRIC [mm]

CAD FILENAME/LAYERS: G03597HN_DC_GB0239KM/03

PANDUIT CORP. TINLEY PARK, ILLINOIS

HST THICK WALL ADHESIVE LINED HEAT SHRINK

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:
(.X) ±0.05 [1.3] (.XXX) ±0.010 [0.25]
(.XX) ±0.02 [0.5] ANGLES ± 5°

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION.

DRAWN BY: LEF	MAT'L: SEE NOTES	SCALE: NONE	
DATE: 10/12/10		DRAWING NO.: GB0239KM	DWG: A SIZE
CHK'D: JVL			