

CAT-3-ACH

CAT-3-1-INCH • CAT-3-CORELESS

The CAT-3-SPECIALTY Rewinder Series provides the ability to load and wind onto non-standard diameter cores through the use of Fin-Style and Adjustable Core Holders. The CAT-3-ACH allows you to wind on any core diameter between 1" - 4" as well as corelessly. The optional APG-CAT guide aligns the outer edge of the label roll as it's being rewound.



CAT-3-ACH

Technical Specifications	CAT-3-1 INCH	CAT-3-ACH	CAT-3-CORELESS
Max Roll Diameter (in)	12 (305-mm)	11 (279-mm)	12 (305-mm)
Core Diameter (in)	1 (25-mm)	1 - 4 (25 - 102-mm) ¹	N/A
Max Media Width (in)	6 (152-mm)		
Max Roll Weight (lbs)	20 (9-kg)	17 (8-kg)	20 (9-kg)
Dimensions-HWD (in)	14 x 12 x 17 (356 x 305 x 432-mm)		
Weight (lbs)	25 (11.3-kg)	27 (12.2-kg)	25 (11.3-kg)
Max Speed (ips)	240 (6096-mm)	230 (5842-mm)	240 (6096-mm)
Min Speed (ips)	0.5 (13-mm)		
Max Torque (in-oz) ^{2,3}	183		
Max RPM ²	388		
Number of Flanges	2	1	2
Power Specifications ²	120 - 220VAC in, 12VAC 40W Out		
Warranty	5 year limited warranty on Rewinder - 1 year limited warranty on Power Adaptor		
Available Options	<ul style="list-style-type: none"> • HTO-CAT (Hi-Torque Option) • LTO-CAT (Lw-Torque Option) • FOOTSWITCH 	<ul style="list-style-type: none"> • APG-CAT (Paper Guide) • HTO-CAT (Hi-Torque Option) • LTO-CAT (Lw-Torque Option) • FOOTSWITCH 	<ul style="list-style-type: none"> • HTO-CAT (Hi-Torque Option) • LTO-CAT (Lw-Torque Option) • FOOTSWITCH

1. The **CAT-3-ACH** can also rewind corelessly.

2. **HTO-CAT** increases Max Torque to 228 in-oz, Max RPM to 485, 304 ips (7,721-mm), and Power Out to 19VDC 80W.

3. **LTO-CAT** decreases Torque Range to 172 - 35 in-oz.