



- RDI PN: 3032S - X - X - XX - X - NL  
 (A) 1 2 3 4 5 6
- 1- SERIES
  - 2- # OF JACKS (2-4)
  - 3- NUMBER OF POSITIONS ( 8 )
  - 4- NUMBER OF CONTACTS (2,4,6,8)
  - 5- PLATING: 1 = 6u" Gold, 2 = 15u" Gold  
 3 = 30u" Gold, 4 = 50u" Gold
  - 6- NL = ROHS COMPLIANT

MATERIAL:  
 HOUSING: PBT POLYESTER UL94V-0  
 MIXED GLASS FIBER  
 STANDARD COLOR-BLACK  
 CONTACTS: 0.35mm THICK PHOS-BRONZE  
 PLATED WITH HARD GOLD AND  
 GOLD FLASH IN SOLDER AREA  
 .MATEL SHIELD-0.25mm THICK COPPER ALLOY  
 PLATED WITH NICKEL  
 CAVITY CONFIRMS TO FCC RULES AND  
 REGULATIONS PART 68, SUBPART F.

NOTE: ALL DIMS ARE IN mm

PROJECTION	
SCALE	N/A
TOLERANCE	EXCEPT AS NOTED
DEC. MILLIMETERS	0.01±0.25 0.00±0.13 0.000±0.05
TITLE	RJ45 GANGED JACK/FULLY SHIELDED W/GROUNDING TABS-ROHS COMPLIANT (A)
DR.	Jlh
DATE	04/07/08
REF.	P/N:3032S-X-X-XX-X-NL
PRE-CK.	GM
DRAWING NO.	3415
SIZE	A
REV.	1 OF 1
SHEET	1

THIS DOCUMENT IS OWNED BY, AND THE INFORMATION CONTAINED IN IT IS PROPRIETARY TO, RDI. BY RECEIPT HEREOF THE HOLDER AGREES NOT TO USE THE INFORMATION AND NOT TO DISCLOSE IT TO ANY THIRD PARTY, NOR REPRODUCE THIS DOCUMENT WITHOUT THE WRITTEN CONSENT OF RDI. AND AGREES TO RETURN THIS DOCUMENT UPON REQUEST.

ECN#	DATE	SYM	REVISION RECORD	AUTH	BY	ANG.
16-072	18/09/16	A	REVISION THE RDI P/N REVISION RECORD	Vicky Tho		40°-30'