


THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO J.S.T. AND SHALL NOT BE USED OR SHOWN WITHOUT WRITTEN PERMISSION.

Item No.	Part No.	Description
1	See Table 1	XAF Connector
2	UL10002, 22 AWG	Black
Electrical Specifications		
Current: 3.0AAC/DC		
Voltage: 150V AC/DC		

TABLE 1				
ITEM	NUMBER OF CIRCUITS	CONNECTOR PART NO.	ASSEMBLY PART NO.	TOTAL WIRE REQUIRED
1	2	02XAF-2S	A02XAF02XAF22K102B	258.4 mm
1	3	03XAF-2S	A03XAF03XAF22K102B	387.6 mm
1	4	04XAF-2S	A04XAF04XAF22K102B	516.8 mm
1	5	05XAF-2S	A05XAF05XAF22K102B	646 mm
1	6	06XAF-2S	A06XAF06XAF22K102B	775.2 mm
1	8	08XAF-2S	A08XAF08XAF22K102B	1,033.6 mm
1	10	10XAF-2S	A10XAF10XAF22K102B	1,292 mm
1	20	20XAF-2S	A20XAF20XAF22K102B	2,584 mm



All dimensions are in millimeters with a default tolerance of +/- 5.0 unless otherwise specified.		CUSTOMER NAME			
		DESCRIPTION 2.5mm Pitch XAF Standard Catalog Assembly - 4" Overall Length - Pin Out: 1 to N			
Drawn By: Larissa Mosley	Checked By: Steven Pilkington	SIZE	CUSTOMER PART NO.	PART NO.	REV
SCALE 1:1		DRAWING NO. GAM-544		DATE 6/21/2018	

ZONE	REV	DESCRIPTION	DATE	APPROVED
	1	Add Electrical Specifications	6/29/2018	LM