


Tous droits strictement réservés. Reproduction ou communication a des tiers interdite sous quelque forme que ce soit sans autorisation écrite du propriétaire. Propriété de ©BERG ELECTRONICS. Droits de reproduction BERG ELECTRONICS INC.

All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of ©BERG ELECTRONICS Copyright BERG ELECTRONICS INC.



PRODUCT NO.	DIM "X"		
	4.25±0.1	3.5±0.1	5.0±0.1
73590-001	OTHERS	36,67	1,17,34,35,51,68
73590-001LF	OTHERS	36,67	1,17,34,35,51,68



NOTES

- ① MATERIAL
HOUSING : LCP UL94V-0 BLACK.
PIN : PHOSPHOR BRONZE.
- ② FINISH - PIN
UNDER PLATING : 0.5um Ni.
CONTACT AREA : 0.1um GOLD OVER
 0.5um Pd-Ni
SOLDER TAIL : 2.5um Sn-Pb.
 : 2.5um PURE Sn (FOR -001LF)
- 3 RECOMMENDED SCREW TORQUE 1.0 TO 1.5 MAX in-lbs. (1.2-1.7 cm-kgs).
RECOMMENDED HOLD-DOWN: 2mm SCREWS (95121) AND HEX NUTS (92869-001).
- 4 IF LEAD FREE P.N.THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION WITH A 1.00MM MINIMUM THICK CIRCUIT BOARD.
- 5 IF LEAD FREE P/N.THE PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008
- 6 LEAD FREE P/N PACKAGING MEETS GS-14-920 SPECIFICATION

mat'l. code				tolerances unless otherwise specified		CUSTOMER COPY		 www.fciconnect.com	
ltr	ecn no	dr	date	linear	.X ±.3	projection		title	
A	V70945	RHG	7/22/97		.XX ±.13			68 POS. EJECT	
B	N05-0196	WB	07/05/05	angles	.XXX ±.051	 mm	 scale	product family	
					0° ±2'			A4	PCMCIA
				dr	R.GRAPE	7/22/97		code	
				engr	D BRANN	7/22/97		-	
				chr	D BRANN	7/22/97		sheet	
				appd	D BRANN	7/22/97	1:1	1 of 1	
sheet	revision	B						cage code	
index	sheet	1						2526	