



NOTES:

1. PLUG FINGER SAME AS 290 PLUG.
2. PLUG FINGER, INSULATOR, HANDLE AND FLEX RELIEF SHIPPED UNASSEMBLED.
3. ASSEMBLE FLEX RELIEF TO HANDLE BEFORE INSERTING CABLE.
4. MATERIALS:
 PLUG ASSEMBLY - COPPER ALLOY, NICKEL PLATED
 TERMINALS - COPPER ALLOY, TIN PLATED
 INSULATORS - MYLAR, PHENOLIC AND THERMOPLASTIC
 SCREWS - STEEL, NICKEL PLATED
 HANDLE - ZINC ALLOY, NICKEL PLATED
 FLEX RELIEF - THERMOPLASTIC RUBBER, BLACK
5. THIS PRODUCT IS RoHS COMPLIANT.

PARTNUMBER	RECOMMENDED FLEX RELIEF CABLE RANGE
290F	Ø 0.220 - Ø 0.190 [Ø 5.59 - Ø 4.83]
290FL	Ø 0.250 - Ø 0.220 [Ø 6.35 - Ø 5.59]

CUSTOMER DRAWING

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.									
					SIZE	WIDTH	MULT	LBS/M	TEMPER					
					FINISH			MATERIAL						
					SPEC No.			SPEC No.						
					FIRST USED ON		SCALE 5:4							
					DATE DRAWN	BY	CHKD	APVD						
					6/19/17	AB	AB 6/19/17	TJK 2/16/22						
										SHEET 1 OF 1				
										NAME 290 PLUG WITH SLEEK HANDLE AND FLEX RELIEF, RoHS				
UNLESS OTHERWISE SPECIFIED 1. ALL DIMENSIONS IN INCHES [mm] - TWO PLACE DECIMALS ±0.02 [0.5] - THREE PLACE DECIMALS ±0.005 [0.13]					DO NOT SCALE DRAWING									

REVISIONS

SolidWorks CAD File

