



VEHICULAR 4-PORT MIMO ANTENNA VLQ69273X22N

698-960 / 1710-2700 / 2300-2700 / 4900-5900 MHZ

The Laird vehicular 4-port MIMO antenna covers the 698-960 / 1710-2700 MHz, 2300-2700 / 4900-5900 MHz. The VLQ69273x22N is configured with 4-port, dual-band elements. Connector options include SMA male connectors for 3G/4G LTE with RSMA male connectors for the WiFi port. The housing incorporates a low-profile, rugged design that meets IP67 standards. The antenna also features high impact, UV-resistant polycarbonate plastic available in black or white.

SPECIFICATIONS

PARAMETER	PERFORMANCE			
Model Number	VLQ69273B22N-518A (Black)		VLQ69273W22N-518A (White)	
No. of Ports	4 (2-ports 3G/4G LTE, 2-ports WiFi)			
	3G/4G (LTE) Ports		WiFi Ports	
Frequency Bands (MHz)	698-960 MHz	1710-2700 MHz	2300-2700 MHz	4900-5900 MHz
Peak Gain * dBi	3.2	4.5	5.5	6.3
Max Gain +/- 30o above horizon	N/A	N/A	N/A	4.8
VSWR* Typical	< 1.8:1	< 1.9:1	< 2.0:1	< 1.6:1
VSWR* Max	< 2.0:1	< 2.0:1	< 2.0:1	< 2.0:1
Typical Port-to-Port Isolation*	698-960	1710-2700	2300-2700	4900-5900
LTE1-to-LTE2	> 14 dB	> 20 DB	> 23DB	N/A
LTE1-to-WiFi	> 23 DB	> 20 DB	> 20 DB	> 40 DB
LTE2-to-WiFi	> 23 DB	> 20 DB	> 20 DB	> 38 DB
LTE1-to-LTE2	> 25 DB	> 19 DB	> 20 DB	> 36 DB
LTE1-to-WiFi	> 23 DB	> 20 DB	> 21 DB	> 39 DB
LTE2-to-WiFi	N/A	N/A	> 20 DB	> 26 DB

*Measured on 1 ft. (30.48 cm) diameter ground plane

PARAMETER	PERFORMANCE
Nominal Impedance	50 Ω
Polarization	Vertical Linear
Azimuth Beam Width	Omnidirectional
Input Power, Max	50 Watt (ambient temp. of 25°C / 77°F)
Operating Temperature	-30°C - +70°C (-22°F to +158°F)
Dimensions (dia. x hgt)	132 mm x 75 mm (5.2" x 2.9")
Weight	Approximately 1.04 kg (2.29 lbs)
Connector	SMA-Male (3G/4G LTE port) RSMA-Male (WiFi port)
Cable (exposed length)	LMR®-195 or equivalent- 518.2 cm (17 ft)
Radome / Baseplate Material	PC, UL94 - V0 Rating, UV Stable
Material Compliance	ROHS compliant
IP Dust & Water Ingress Rating	IP67

*Measured on 1 ft. (30.48 cm) diameter ground plane

PART NUMBER	
VLQ69273B22N-518A	2-Ports 4G/LTE: SMA Male; 2 Ports WiFi:RSMA Male(Black)
VLQ69273W22N-518A	2-Ports 4G/LTE: SMA Male; 2 Ports WiFi:RSMA Male(White)

TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

te.com

TE, and TE connectivity (logo) are trademarks owned or licensed by the TE Connectivity Ltd. family of companies. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

TE Connectivity warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations TE Connectivity will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the TE Connectivity product is installed. Useful lifetime of the original end product may vary but is not warranted to exceed one (1) year from the original date of the end product purchase.

©2022 TE Connectivity. All Rights Reserved.

08/22 Original