

Connector set - HC-EVO-B24PT-BWD-HH-M32ELC-AL - 1411490

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



EVO connector set, B24, metal housing, consisting of sleeve housing 1411472, panel mounting base 1411331, EVO screw connection 1411440, pin contact insert 1407736, socket contact insert 1407735.



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	800.0 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

General

Number of positions	24+PE
Type	B24
Connection method	Push-in connection
Cable exit	straight
Degree of protection for housing	IP66
	IP69K (ISO 20653:2013-02)
	4
	4X
	12
Connection method	Push-in connection
Rated voltage (III/3)	500 V
Rated surge voltage	6 kV
Rated current	16 A

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Connector set - HC-EVO-B24PT-BWD-HH-M32ELC-AL - 1411490

Articles in set

Contact insert - HC-B 24-I-PT-F - 1407735



HEAVYCON socket insert, B24 series, 24 + PE-pos., push-in connection

Contact insert - HC-B 24-I-PT-M - 1407736



HEAVYCON pin insert, B24 series, 24 + PE-pos., push-in connection

Cable gland - HC-B-G-M32-EC-AL - 1411440



EVO EMC cable gland with bayonet locking, B series, size M32, cable diameter: 14 - 21 mm

Housing - HC-EVO-B24-HHFD-EL-AL - 1411472



HEAVYCON EVO sleeve housing, EMC version, without powder coating, with bayonet flange for EVO screw connection, B24, for double locking latch, height: 88 mm, without EVO screw connection.

Housing - HC-STA-B24-BWD-ELC-AL - 1411331



HEAVYCON B24 panel mounting base, with double locking latch, with flat gasket, salt-water-resistant aluminum, conductive profile gasket

Connector set - HC-EVO-B24PT-BWD-HH-M32ELC-AL - 1411490

Classifications

eCl@ss

eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 8.0	27440101

ETIM

ETIM 4.0	EC002641
ETIM 5.0	EC002636

Approvals

Approvals

Approvals

EAC

Ex Approvals


Approvals submitted

Approval details

EAC


Drawings

Schematic diagram



Pin assignment, connection side, pin


Schematic diagram



Pin assignment, connection side, socket


Connector set - HC-EVO-B24PT-BWD-HH-M32ELC-AL - 1411490

Diagram




Derating diagram

Dimensional drawing



Dimensional drawing

Dimensional drawing



Panel cutout