



ITEM	DESCRIPTION	MATERIAL	FINISH
11	ID LABEL	POLYPROPYLENE	CLEAR, (LABEL DETAIL)
10	OVERMOLD	TPE	SEE P/N CHART
9	SOCKET CONTACT	Cu ALLOY	GOLD PLATED
8	WIRE, 18AWG (UL1015)	PVC INSULATION	SEE FACE VIEWS
7	FEMALE COUPLING	ZINC DIE-CAST	BLACK E-COAT
6	FRICITION RING	NYLON	WHITE
5	FEMALE INSERT	TPE	SEE P/N CHART
4	MALE COUPLING	ZINC DIE-CAST	BLACK E-COAT
3	M/F CONTACT (GROUND)	Cu ALLOY	GOLD PLATED
2	M/F CONTACT (SIGNAL)	Cu ALLOY	GOLD PLATED
1	MALE INSERT	TPE	SEE P/N CHART

(A) NOTES:  
 1. MATERIAL: AS NOTED  
 2. FINISH: AS NOTED  
 3. ELECTRICAL:  
 VOLTAGE: 483V PER IEC60664  
 600V PER UL2238  
 CURRENT: 10A  
 4. TEMP RATING: -20°C TO +80°C  
 5. PROTECTION: IP67 (WHEN MATED)  
 6. COUPLING THREADS: 7/8-16UN  
 7. UL LISTED FILE: E152210  
 8. ALL DIMS ARE FOR REFERENCE UNLESS TOLERANCED OR NOTED OTHERWISE

PART NO.	ENG. NO.	O-MOLD & INSERT COLOR	LABEL PRINT COLOR
1300350115	DNETAUXPTG	BLACK	WHITE
1300350085	DNETAUXPT	YELLOW	BLACK

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC: REDRAW TO NX, ADD BOM TABLE, UPDATE NOTES, REMOVE CENEL, ORIENT VIEWS TO MATCH MFG DOC	
$F_A = 0$ $F_E = 0$ $F_P = 0$	DIMENSION UNITS	SCALE		
DIVISIONAL SYMBOLS	INCH 2:1 GENERAL TOLERANCES (UNLESS SPECIFIED)	MM INCH	INITIAL REVISION: DRWN: DRWN BY 0099/99/99 APPR: APPR BY 0099/99/99	<b>molex</b> MINI-CHANGE TEE 4 POLE MALE/FEM TRUNK, 4 POLE FEMALE DROP SINGLE KEY PRODUCT CUSTOMER DRAWING
4 PLACES ± ± 3 PLACES ± ± 2 PLACES ± ± 1 PLACE ± ± 0 PLACES ± ± ANGULAR TOL ± °	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	THIRD ANGLE PROJECTION	SERIES 130035	
RELEASE STATUS P1 RELEASE DATE 2022/04/11 21:32:33	DOCUMENT NUMBER 1300350085 DOC TYPE PSD DOC PART 000 REVISION A		MATERIAL NUMBER CUSTOMER	SHEET NUMBER 1 OF 1