5413476-2 - ACTIVE

TE Internal #: 5413476-2 BNC RF Interface, Jack, 50 Ω, Bayonet, 1 GHz Operating Frequency, Cable-to-Board, 1 Position, Printed Circuit Board, Panel Mount

View on TE.com >



Connectors > RF Connectors > Coax Connectors



RF Interface: BNC

RF Connector Style: Jack

RF Connector Mated Outer Diameter (Approximate): 14.53 mm [.572 in]

Impedance: 50Ω

RF Connector Coupling Mechanism: Bayonet

Features

Product Type Features

RF Interface	BNC
RF Connector Style	Jack
Connector System	Cable-to-Board
Sealable	No

Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
PCB Mount Orientation	Vertical
Number of Positions	1
Number of Coaxial Contacts	1
Electrical Characteristics	
Impedance	50 Ω
Body Features	
Body Material	Zinc
Body Plating Material	Nickel
Contact Features	
RF Connector Center Contact Underplating Material	Nickel
	30 µin
RF Connector Center Contact Plating Material	Gold

BNC RF Interface, Jack, 50 Ω , Bayonet, 1 GHz Operating Frequency, Cable-to-Board, 1 Position, Printed Circuit Board, Panel Mount



RF Connector Center Contact Material	Phosphor Bronze
Termination Features	
Termination Post & Tail Length	5.72 mm[.225 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
PCB Mount Retention	With
Panel Mount Feature Type	Lockwasher and Nut
RF Connector Coupling Mechanism	Bayonet
Connector Mounting Type	Panel Mount
RF Contact Captivation Method	Mechanical
Detent	With
Dimensions	
Mounting Post Length	3.48 mm[.137 in]
Profile Height from PCB	35.56 mm[1.4 in]
RF Connector Mated Outer Diameter (Approximate)	14.53 mm[.572 in]

Operating Temperature Range

-55 – 85 °C[-67 – 185 °F]

Operation/Application

Operating Frequency	1 GHz
Packaging Features	
Packaging Method	Tube
Other	
Grade	Commercial
Dielectric Material	Polymethylpentene
Product Compliance For compliance documentation, visit the product page on TE.com>	
·	Compliant with Exemptions
For compliance documentation, visit the product page on TE.com>	Compliant with Exemptions Compliant with Exemptions
For compliance documentation, visit the product page on TE.com> EU RoHS Directive 2011/65/EU	

BNC RF Interface, Jack, 50 Ω, Bayonet, 1 GHz Operating Frequency, Cable-to-Board, 1 Position, Printed Circuit Board, Panel Mount



Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC

Not Low Halogen - contains Br or Cl > 900 ppm.

Wave solder capable to 265°C

Halogen Content

Solder Process Capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts






Customers Also Bought

BNC RF Interface, Jack, 50 Ω, Bayonet, 1 GHz Operating Frequency, Cable-to-Board, 1 Position, Printed Circuit Board, Panel Mount







TE Part #5176264-9 AMPMODU 2MM V 20P AU:0.2 BLACK LF

Documents

Product Drawings JACK, DECOUPLER, PCB, VERT, BNC

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5413476-2_F_c-5413476-2-f.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_5413476-2_F_c-5413476-2-f.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5413476-2_F_c-5413476-2-f.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages

C For support call+1 800 522 6752

BNC RF Interface, Jack, 50 Ω, Bayonet, 1 GHz Operating Frequency, Cable-to-Board, 1 Position, Printed Circuit Board, Panel Mount



Decoupled Connectors

English

Product Specifications Application Specification

English