

GloTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: NEMA 6-15P, 2 CONDUCTOR + GROUND PLUG, APPROVALS: EL-161, E119066 to , GT Cable #144: 18 / 3 Conductors, 6.3mm OD, SVT, 60 Deg.C, 300V, BLK/WHT/GRN, Approvals: , 2410±50mm, GlobTek Black
	Model No. Power Cord
Part No./Ordering No. 3611448F00T(R)	Rev B1

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

In Addition to GlobTek Inc.'s renewed ISO9001:2008 - Quality Management System Certification, GlobTek Inc. is now certified to:

ISO13485:2003 - Medical Devices Quality Management System Certification  
ISO14001:2004 - Environmental Management System Certification

ISO Certificates are available online at <https://www.globtek.com/iso-certificates/>  
Prop 65 Statement:<https://en.globtek.com/prop-65-statement.pdf>

The acceptance of this specification and use of the product described in this document indicates the acceptance and binding of the customer to Globtek TERMS AND CONDITIONS (attached to the end of this document), which supersede all other agreements, terms, and conditions (<https://en.globtek.com/terms-and-conditions/>).

The purchaser of this product (Customer) agrees that it is their sole responsibility to determine suitability/fitness of the product described in this specification for their application and to take precautions for protection against any hazards attendant to the handling and use of the product.

**Footnote:**

GlobTek Inc. will not be liable for the safety and performance of these power supplies if unauthorized access and repair occurs. End user should consult applicable UL, CSA or EN standards for proper installation instruction.

**Limitation of Use:**

GlobTek products are intended for use with commercial, medical, and/or industrial equipment only. GlobTek product are not authorized for use as mission critical components in life support hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of GlobTek Inc.  
Contents of this document are subject to change without prior notice.

**Customer Approval of Specification:**

Please approve, sign and send back to GlobTek so we can complete order processing.  
A delay in receipt of this form will delay delivery schedule.

Company Name: _____	Customer P/N: _____
Quote Number: _____	Date: _____
Authorized Representative Name: _____	Authorized Representative Signature: _____

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: NEMA 6-15P, 2 CONDUCTOR + GROUND PLUG, APPROVALS: EL-161, E119066 to , GT Cable #144: 18 / 3 Conductors, 6.3mm OD, SVT, 60 Deg.C, 300V, BLK/WHT/GRN, Approvals: , 2410±50mm, GlobTek Black	
	Model No. Power Cord	
Part No./Ordering No. 3611448F00T(R)		Rev B1

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

## REVISION HISTORY

REV	DESCRIPTION	SUB	DATE	APPROVED
B1	Add Overall rating 15A/250VAC	QA	06/03/2021	QA
B	Update to SF format	QA	05/24/2021	QA

**Cordset Information:**

CordsetColor:GlobTek Black

Cord Length (mm):2410±50


**NOTES:**

Cord, Plug and Connector must be marked with approval symbols of file number(s)


GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: NEMA 6-15P, 2 CONDUCTOR + GROUND PLUG, APPROVALS: EL-161, E119066 to , GT Cable #144: 18 / 3 Conductors, 6.3mm OD, SVT, 60 Deg.C, 300V, BLK/WHT/GRN, Approvals: , 2410±50mm, GlobTek Black	
	Model No. Power Cord	
Part No./Ordering No. 3611448F00T(R)		Rev B1

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

END A



END B



WHITE (NEUTRAL) - STRIPPED


BLACK (LINE) - STRIPPED

GREEN (GROUND) - # 10 RING NON-INSULATED OR EQUIV.

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: NEMA 6-15P, 2 CONDUCTOR + GROUND PLUG, APPROVALS: EL-161, E119066 to , GT Cable #144: 18 / 3 Conductors, 6.3mm OD, SVT, 60 Deg.C, 300V, BLK/WHT/GRN, Approvals: , 2410±50mm, GlobTek Black	
	Model No. Power Cord	
Part No./Ordering No. 3611448F00T(R)		Rev B1

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

CABLE IMAGE



GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: NEMA 6-15P, 2 CONDUCTOR + GROUND PLUG, APPROVALS: EL-161, E119066 to , GT Cable #144: 18 / 3 Conductors, 6.3mm OD, SVT, 60 Deg.C, 300V, BLK/WHT/GRN, Approvals: , 2410±50mm, GlobTek Black	
	Model No. Power Cord	Rev B1
Part No./Ordering No. 3611448F00T(R)		

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

End A Code:361-A Description:NEMA 6-15P, 2 CONDUCTOR + GROUND PLUG, APPROVALS: EL-161, E119066 Rating (V):250 Rating (A):15.0 Gender:Male Overmolded:Yes	Cable Code:144 Description:GT Cable #144: 18 / 3 Conductors, 6.3mm OD, SVT, 60 Deg.C, 300V, BLK/WHT/GRN, Approvals: Color:GlobTek Black Wire Gauge(AWG):18 Cond:3 Type:SVT Temperature:60° C Amps:10 Volts:300 OD:6.3 ConductorsColors:BLK/WHT/GRN	End B Code:00T-A Description: Rating (V): Rating (A): Gender:N/A Overmolded:No
--	---	--

Overall cable rating:15A/250VAC

Plug Approvals	Cable Approvals	Connector Approvals
----------------	-----------------	---------------------



Note: North American power cords are certified as assemblies of UL rated parts, so, the combination of UL certified plugs, connectors, and cables total up to a UL approved cordset or cable assembly

[LINK TO CERTs](#)  
[Link to live Power Cords listing @ UL](#)  
[Link to live Flexible Cord listing @ UL](#)



UL Note: North American power cords are certified as CSA assemblies of UL rated parts, so, the combination of UL or certified plugs, connectors, and cables total up to a UL or CUL approved cordset or cable assembly

[LINK TO CERTs](#)  
[Link to live Power Cords listing @ UL](#)  
[Link to live Flexible Cord listing @ UL](#)

AGENCY ONLINE DOCUMENTS

<http://en.globtek.com/cordsets/>

PROPRIETARY INFORMATION

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2017 - 2023

quest /10/08/2023 2:42:03 PM

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: NEMA 6-15P, 2 CONDUCTOR + GROUND PLUG, APPROVALS: EL-161, E119066 to , GT Cable #144: 18 / 3 Conductors, 6.3mm OD, SVT, 60 Deg.C, 300V, BLK/WHT/GRN, Approvals: , 2410±50mm, GlobTek Black	
	Model No. Power Cord	
	Part No./Ordering No. 3611448F00T(R)	Rev B1

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

RoHS/RoHS3 Declaration	<a href="https://www.globtek.com/pdf/rohs_cert/01ta000007dRKGAA2">https://www.globtek.com/pdf/rohs_cert/01ta000007dRKGAA2</a>
REACH Declaration	<a href="https://www.globtek.com/pdf/iso_certificates/REACH.pdf">https://www.globtek.com/pdf/iso_certificates/REACH.pdf</a>
Conflict Minerals Declaration	<a href="https://www.globtek.com/pdf/conflict-minerals.pdf">https://www.globtek.com/pdf/conflict-minerals.pdf</a>
Prop 65 Statement	<a href="https://en.globtek.com/prop-65-statement.pdf">https://en.globtek.com/prop-65-statement.pdf</a>
CE.UKCA.Cord	<a href="https://globtek.secure.force.com/spec/ec_decl_product_model_family_incl_cord?id=01ta000007dRKG">https://globtek.secure.force.com/spec/ec_decl_product_model_family_incl_cord?id=01ta000007dRKG</a>
IPXY rating is based on 3rd party testing and customers should check suitability and test system level IPXY rating before ordering.	

PROPRIETARY INFORMATION

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc.


2017 - 2023

quest /10/08/2023 2:42:03 PM

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: NEMA 6-15P, 2 CONDUCTOR + GROUND PLUG, APPROVALS: EL-161, E119066 to , GT Cable #144: 18 / 3 Conductors, 6.3mm OD, SVT, 60 Deg.C, 300V, BLK/WHT/GRN, Approvals: , 2410±50mm, GlobTek Black	
	Model No. Power Cord	
	Part No./Ordering No. 3611448F00T(R)	Rev B1

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

Hanking:361-00T  
 Description:See drawing  
 Image:



Notes/Modifications/Customizations (notes in this section supersede the values shown in the standard spec):