


# **Scotchlok** Terminals

MNG18BCM-A, MNG14BCM-A, MNG10BCM-A



Butt Connector, Nylon Insulated with Insulation Grip, Moisture Resistant

Data Sheet February 2008

Product Number	Wire Range (AWG)	L
MNG18BCM-A	22-18	1.02
MNG14BCM-A	16-14	1.06
MNG10BCM-A	12-10	1.23

**Specifications** Wire Size: See Table Above

Barrel Seam: Butted with insulation Grip
Maximum Voltage Rating: 600 V Building Wire or

1000 Volts Signs or Fixtures (Luminaires)

Maximum Operating Temp: 221°F (105°C)
Maximum Current: Same as Wire
Terminal Material: Copper
Terminal Plating: Tin

Sealant: Petroleum based grease

#### **Installation Information**

### **△WARNING**

Turn power off before installing or removing terminal. All electrical work should be done according to appropriate electrical codes.

Strip away the end 3/8 inch of wire insulation.

Make the crimp the proper station of a recommended  $3M^{TM}$  Scotchlok<sup>TM</sup> Crimp Tool: TH-440, TH-450 (scissor style) or TR-482, TR-490 (ratchet style) hand tools.



Barrel Crimp (Electrical)

Insulation Grip Crimp (required for sealant integrity)

#### **Engineering Specification**

Crimp-type terminals shall, electrically and mechanically, connect to the pre-stripped end of two stranded copper wires.

The connector line shall offer barrel variations in wire (AWG) size (22-18, 16-14, 12-10) and construction (non-insulated brazed seam, vinyl insulated butted seam, nylon insulated seamless, etc.)

The insulator shall be color coded and sized for a specified (AWG) wire range (22-18, 16-14 and 12-10).



#### Caution

Avoid eye and prolonged or repeated skin contact.

### **Suggested First Aid**

In case of eye contact, flush eyes with large amounts of water for at least ten minutes and call a physician

#### **Important Notice**

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

## Warranty; Limited Remedy; Limited Liability:

This product will be free from defects in material and manufacture from the time of purchase.

3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.

3M and Scotchlok are trademarks of 3M Company.



Electrical Markets Division 6801 River Place Blvd. Austin, TX 78726-9000 800 245 3573 FAX 800 245 0329 www.3M.com/electrical

Please recycle. © 3M 2008 All rights reserved. 78-8127-6820-4\_A