

6 5 4 3 2 1

APPROVED: _____
 DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	9/9/20	

15.00
 15.00
 9.50
 9.50
 $\phi 4.30^{+0.08}_{-0.20}$
 $\phi 6.10^{+0.10}_{-0.09}$
 $\phi 19.00$

15.00

8.40
 2.90±0.15
 M8*0.75
 2.15±0.15
 4.00

OPFN1ANNC1BNB	INSERTION LOSS: 0.1dB MAX	PVC Red
OPFN1ANNC1ANB	INSERTION LOSS: 0.2dB MAX	PVC Red
PART NUMBER	DESCRIPTION	Cap Color

SPECIFICATIONS:

Material:
 Housing: ZA#5, rated UL 94V-0
 Cap: PVC, rated UL 94V-0, Color: RED
 Sleeve: Zircomia ceramic
 Electrical:
 Standards of IEC,EIA/TIA, Telcordia
 Repeatability: (500 cycles min): 0.2dB max
 Insertion loss: See Chart
 Interchangeability: See Chart
 Temperature Rating:
 Operating temperature: -40°C to +75°C
 Environmental:
 Lead free, RoHS compliant.

UNLESS OTHERWISE SPECIFIED
 ALL DIMENSIONS ARE MILLIMETERS
 TOLERANCES: EXCEPT AS NOTED

MM	ANGLE
X. ± 0.35	X.° ± 2°
.X ± 0.30	.X° ± 1°
.XX ± 0.25	.XX° ± 0.5°
.XXX ± 0.15	.XXX° ± 0.5°

APPROVALS		DATE
DRAWN	LH	9/9/20
CHECKED	JL	9/9/20
APPROVED		

ADAM TECH INTERCONNECTS
 909 Rahway Avenue,
 Union, NJ 07083
 Phone: 908-687-5000
 Fax: 908-687-5710

TITLE: OPTICAL FC ADAPTERS, 1 PORTS, WITH FC DUST CAP SQUARE WITH POSITIONING HOLE

SIZE X	PART NO. OPFN1ANNC1XNB	REV. -
REF: S00005C	SCALE: NTS	SHEET 1 OF 1

6 5 4 3 2 1