

| | | | | | | | | |
|--|---|---|---|---|---|---|---|--|
| | 1 | 2 | 3 | 4 | 5 | 6 | 7 | |
|--|---|---|---|---|---|---|---|--|

NOTES:
 Plunger: Brass, 20μ" MIN Au over, 50μ" MIN Ni over
 Barrel : Brass, 3μ" ,MIN Au over, 50μ" MIN Ni over
 Spring : Stainless Steel

Mechanical Characteristics:
 Spring Force : 60g ± 20% at Working Length
 Mechanical Life : 1,000,000 cycle

Electrical Characteristics:
 Current Rating : 2A
 Contact Resistance : 20 mΩ Max

Operating Temperature range : -55~125° C
 Packing: PE Bag

| | | | | | | | | | | | | |
|-------|-----------------------------------|-------|--------------|-------|------------|-----|----------------------------------|------------|-------------|------------|--------------|-----------------------------------|
| G | RoHS compliant Unit: mm | | Scale | Free | | | | | Date | Name | Customer-No. | |
| | | | TOLERANCE | | | | | | Drawn | 28.03.2018 | Tom | ASSMANN WSW-No. A-CSL-S-020-B2 |
| | X.X | ±0.20 | | | | | Approved | 28.03.2018 | Winnie | | | |
| | X.XX | ±0.10 | | | | | | | | | | |
| H | X.XXX | ±0.08 | | | | | | | | | Drawing-No. | |
| | DIM | TOL | | | | | ASSMANN WSW components | | ASS 7893 CO | | rev00 | |
| | Angle | ±3° | ① | Drawn | 28.03.2018 | Tom | | | Replace | Sheet | | |
| Angle | TOL | Id. | Modification | Date | Name | | | | | | | |

| | | | | | | | | |
|--|---|---|---|---|---|---|---|--------|
| | 1 | 2 | 3 | 4 | 5 | 6 | 7 | SV4444 |
|--|---|---|---|---|---|---|---|--------|