

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 Fax: (818) 701-4939

Features

- Low Cost
- Lead Free Finish/RoHS Compliant (Note1) ("P"Suffix designates Compliant. See ordering information)
- High Current Capability
- High Voltage
- Halogen free available upon request by adding suffix "-HF"

Maximum Ratings

- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

 ,,, _,, _							
MCC	Device	Maximum	Maximum	Maximum			
Catalog	Marking	Recurrent	RMS	DC			
Number	_	Peak Reverse	Voltage	Blocking			
		Voltage	-	Voltage			
R1200	R1200	1200V	840V	1200V			
R1500	R1500	1500V	1050V	1500V			
R1800	R1800	1800V	1260V	1800V			
R2000	R2000	2000V	1400V	2000V			

Electrical Characteristics @ 25°C Unless Otherwise Specified


Average Forward Current	I _{F(AV)}	500mA	$T_A = 50^{\circ}C$			
Peak Forward Surge Current	I _{FSM}	30A	8.3ms, half sine			
Maximum						
Instantaneous Forward Voltage						
R1200-R1800 R2000	V _F	2.0V 3.0V	I _{FM} = 0.5A; T _A = 50°C			
Maximum DC Reverse Current At Rated DC Blocking Voltage	I _R	5.0μΑ 50μΑ	T _A = 25°C T _A = 100°C			
Typical Junction Capacitance	CJ	30pF	Measured at 1.0MHz, V _R =4.0V			

Note: 1. High Temperature Solder Exemption Applied, see EU Directive Annex 7.

-www.mccsemi.com

R1200 THRU R2000

500 Milliamp High Voltage Silicon Rectifier 1200 to 2000 Volts



Revision: B

DIM


А

В


2013/01/01




R1200 - R2000



Instantaneous Reverse Current - Micro Ampsversus Percent Of Rated Peak Reverse Voltage - Volts



Average Forward Rectified Current - Amperes/ersus Ambient Temperature -°C



Peak Forward Surge Current - Amperesversus Number Of Cycles At 60Hz - Cycles

-www.mccsemi.com



Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel: 5Kpcs/Reel
Part Number-AP	Ammo Packing: 5Kpcs/Ammo Box
Part Number-BP	Bulk: 50Kpcs/Carton

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com