




H
G
F
E
D
C
B
A




B1 TYPE




TOP ENTRY LAYOUT




BOTTOM ENTRY LAYOUT




B1 TYPE




B2 TYPE





TOP ENTRY LAYOUT



BOTTOM ENTRY LAYOUT



B2 TYPE



Recommended PCB Layout

General Tolerance: ±0.05

☐ Solder Area

Specifications

Material
Contact : Phosphor Bronze
Insulator :
Standard: Polymer, LCP, UL 94-V0

Plating
See Ordering Grid


Electrical
Current Rating : 1 Amp Per Pin
Insulation Resistance: 1000 MΩ min
Contact Resistance: 40 mΩ max.
Dielectric Withstand Voltage: AC 300 V

Mechanical & Environmental
Operating Temperature: -40°C to +105°C

Soldering Process:
LCP (Standard) -
IR Reflow : 260°C for 10 sec.
Wave :250°C for 5-10 sec
Manual Solder: 350°C for 3-5 sec

Mates with (Subject to pin length)
BC020 BC025 BC030 BC032
BC034 BC090

Ordering Grid



No. of Contacts
02 to 40

Contact Plating
A = Gold Flash All Over (Standard)
C = Tin All Over

Request Samples and Quotation

Packing Options
C = Tape and Reel with Film (Standard)
D = Tube
F = Tube with Film

Insulator Material
L = LCP (Standard)

Type
1 = B1 Type
2 = B2 Type

No. of Contacts	Dimensions	
	A	B
2	1.00	2.50
3	2.00	3.50
4	3.00	4.50
5	4.00	5.50
6	5.00	6.50
7	6.00	7.50
8	7.00	8.50
9	8.00	9.50
10	9.00	10.50
11	10.00	11.50
12	11.00	12.50
13	12.00	13.50
14	13.00	14.50
15	14.00	15.50
16	15.00	16.50
17	16.00	17.50
18	17.00	18.50
19	18.00	19.50
20	19.00	20.50
21	20.00	21.50
22	21.00	22.50
23	22.00	23.50
24	23.00	24.50
25	24.00	25.50
26	25.00	26.50
27	26.00	27.50
28	27.00	28.50
29	28.00	29.50
30	29.00	30.50
31	30.00	31.50
32	31.00	32.50
33	32.00	33.50
34	33.00	34.50
35	34.00	35.50
36	35.00	36.50
37	36.00	37.50
38	37.00	38.50
39	38.00	39.50
40	39.00	40.50

For bottom entry applications, stringent soldering control & pin alignment are required as lead to pad misalignment could cause incorrect mating.

Part Number BC070		Product Description 1.00mm Pitch Socket, Single Row, Surface Mount, Vertical, Dual Entry	
Drawing Date 20th May 2008			
By	CC	Tolerances (Except as Noted)	Units: Metric (mm)
Detail	BC070 D PCN	Length X. ± 0.30 X.X ± 0.25 X.XX ± 0.15 X.XXX ± 0.10	Angle X.° ± 5° X.X° ± 3° X.XX° ± 2° X.XXX° ± 1°
Revision	D1		3rd Angle Projection
Date	19/07/17		



This drawing is confidential and copyright of Global Connector Technology, Ltd (GCT). This drawing must not be copied or disclosed without written consent. E & OE



www.gct.co

Not to Scale	Drawn By ASE	Sheet No. 1/1
--------------	--------------	---------------