

Lilliput 669GL-70NP/C/T - 7" HDMI Touchscreen monitor

| | |
|--------------------------|---------------------------|
| Screen Size (diagonal) | 7 inches |
| Aspect Ratio | 16:9 |
| Native Resolution | 800×480 (native) |
| Maximum Resolution | 1920×1080 (maximum) |
| Pixel Pitch (mm) | 0.0635×0.190 |
| Scan Frequency (Hz) | 60-72 |
| Response Time (ms) | 15 |
| Viewing Angle (degrees) | 130° x, 120° y |
| Brightness Ratio (cd/m2) | 250 |
| Contrast Ratio | 500:1 |
| Backlight | LED |
| Video Inputs | HDMI, DVI, VGA, composite |
| Audio Outputs | Internal Speaker |
| Touchscreen Technology | 4-wire resistive, USB |
| Input Power | DC 12V |

| | |
|------------------------|---|
| Mounting Options | VESA 75, ¼ inch BSW thread, vertical slot mount mechanism |
| Contents Of Box | |
| Product | 1 x 669GL-70NP/C/T monitor |
| Connection Cables | 1x HDMI (touch) cable, 1x Composite break-out cable, 1x VGA (touch) breakout cable |
| Power Adaptor | 1x DC 12V plug (available in UK, US and EU style), 1x in-car cigarette lighter DC 12V adapter |
| Mounts and stands | 1x Adhesive Lilliput stand |
| Additional accessories | 1x Full-function infrared remote control with battery |
| Dimensions | |
| Height (mm) | 122 |
| Width (mm) | 185 |
| Depth (mm) | 32 |
| Weight (g) | 495 |