

MSCSM120AM11CT3AG
Datasheet

Phase Leg SiC MOSFET Power Module

January 2020



Contents

1 Revision History.....	1
1.1 Revision 1.0.....	1
Product Overview.....	2
2.1 Features.....	3
2.2 Benefits.....	3
2.3 Applications.....	3
Electrical Specifications.....	4
3.1 SiC MOSFET Characteristics (Per MOSFET).....	4
3.2 SiC Schottky Diode Ratings Characteristics (Per SiC Diode).....	6
3.3 Thermal Package Characteristics.....	6
3.4 Typical SiC MOSFET Performance Curves.....	8
3.5 Typical SiC Diode Performance Curves.....	11
Package Specifications.....	12

Tables

Table 1 • Absolute Maximum Ratings.....	4
Table 2 • Electrical Characteristics.....	4
Table 3 • Dynamic Characteristics.....	5
Table 4 • Body Diode Ratings and Characteristics.....	5
Table 5 • SiC Schottky Diode Ratings and Characteristics.....	6
Table 6 • Package Characteristics.....	6
Table 7 • Temperature Sensor NTC1.....	7

Figures

Figure 1 • MSCSM120AM11CT3AG Electrical Schematic.....	2
Figure 2 • MSCSM120AM11CT3AG Pinout Location.....	2
Figure 3 • Maximum Thermal Impedance.....	8
Figure 4 • Output Characteristics, $T_J = 25\text{ }^{\circ}\text{C}$	8
Figure 5 • Output Characteristics, $T_J = 175\text{ }^{\circ}\text{C}$	8
Figure 6 • Normalized RDS(on) vs. Temperature.....	8
Figure 7 • Transfer Characteristics.....	8
Figure 8 • Switching Energy vs. R_g	9
Figure 9 • Switching Energy vs. Current.....	9
Figure 10 • Capacitance vs. Drain Source Voltage.....	9
Figure 11 • Gate Charge vs. Gate Source Voltage.....	9
Figure 12 • Body Diode Characteristics, $T_J = 25\text{ }^{\circ}\text{C}$	9
Figure 13 • 3rd Quadrant Characteristics, $T_J = 25\text{ }^{\circ}\text{C}$	9
Figure 14 • Body Diode Characteristics, $T_J = 175\text{ }^{\circ}\text{C}$	10
Figure 15 • 3rd Quadrant Characteristics, $T_J = 175\text{ }^{\circ}\text{C}$	10
Figure 16 • Operating Frequency vs. Drain Current.....	10
Figure 17 • Maximum Thermal Impedance.....	11
Figure 18 • Forward Characteristics.....	11
Figure 19 • Capacitance vs. Reverse Voltage.....	11
Figure 20 • Package Outline.....	12

1 Revision History

The revision history describes the changes that were implemented in the document. The changes are listed by revision, starting with the most current publication.

1.1 Revision 1.0

Revision 1.0 is the initial release of this document, published in January 2020.

2 Product Overview

The MSCSM120AM11CT3AG is a phase leg 1200 V/254 A full Silicon Carbide power module.

Figure 1 • MSCSM120AM11CT3AG Electrical Schematic





Figure 2 • MSCSM120AM11CT3AG Pinout Location



Pins 25 to 28 must be shorted together

Pins 13 to 16 must be shorted together

Pins 18/19/20/22 must be shorted together

All ratings at $T_J = 25^\circ\text{C}$ unless otherwise specified.

Caution: These devices are sensitive to electrostatic discharge. Proper handling procedures should be followed.

2.1 Features

The following are key features of the MSCSM120AM11CT3AG device:

- SiC Power MOSFET
 - High-speed switching
 - Low RDS(on)
 - Ultra low loss
- Silicon carbide (SiC) Schottky diode
 - Zero reverse recovery
 - Zero forward recovery
 - Temperature-independent switching behavior
 - Positive temperature coefficient on VF
- Low stray inductance
- Kelvin source for easy drive
- Internal thermistor for temperature monitoring
- Aluminum nitride (AlN) substrate for improved thermal performance

2.2 Benefits

The following are benefits of the MSCSM120AM11CT3AG device:

- High efficiency converters
- Outstanding performance at high frequency operation
- Direct mounting to heatsink (isolated package)
- Low junction-to-case thermal resistance
- Solderable terminals both for power and signal for easy PCB mounting
- Low profile
- RoHS Compliant

2.3 Applications

The MSCSM120AM11CT3AG device is designed for the following applications:

- Welding converters
- Switched Mode Power Supplies
- Uninterruptible Power Supplies
- EV motor and traction drive

3 Electrical Specifications

This section shows the electrical specifications of the MSCSM120AM11CT3AG device.

3.1 SiC MOSFET Characteristics (Per MOSFET)

This section describes the electrical characteristics of the MSCSM120AM11CT3AG device.

Table 1 • Absolute Maximum Ratings

Symbol	Parameter	Maximum Ratings		Unit
V_{DSS}	Drain-source voltage	1200		V
I_D	Continuous drain current	$T_C = 25^\circ\text{C}$	254 ¹	A
		$T_C = 80^\circ\text{C}$	202 ¹	
I_{DM}	Pulsed drain current	500		
V_{GS}	Gate-source voltage	−10/25		V
R_{DSon}	Drain-source ON resistance	10.4		$\text{m}\Omega$
P_D	Power dissipation	$T_C = 25^\circ\text{C}$	1067	W

Note:

1. Specification of SiC MOSFET device but output current must be limited due to the size of power connectors.

Table 2 • Electrical Characteristics

Symbol	Characteristic	Test Conditions		Min	Typ	Max	Unit
I_{DSS}	Zero gate voltage drain current	$V_{GS} = 0 \text{ V}; V_{DS} = 1200 \text{ V}$			30	300	μA
R_{DSon}	Drain–source on resistance	$V_{GS} = 20 \text{ V}$ $I_D = 120 \text{ A}$	$T_J = 25^\circ\text{C}$		8.4	10.4	$\text{m}\Omega$
			$T_J = 175^\circ\text{C}$		13.4		
$V_{GS(th)}$	Gate threshold voltage	$V_{GS} = V_{DS}, I_D = 3 \text{ mA}$		1.8	2.8		V
I_{GSS}	Gate–source leakage current	$V_{GS} = 20 \text{ V}, V_{DS} = 0 \text{ V}$				300	nA

Table 3 • Dynamic Characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
C_{iss}	Input capacitance	$V_{GS} = 0 \text{ V}$ $V_{DS} = 1000 \text{ V}$ $f = 1 \text{ MHz}$		9060		pF
C_{oss}	Output capacitance			810		
C_{rss}	Reverse transfer capacitance			75		
Q_g	Total gate charge	$V_{GS} = -5/20 \text{ V}$ $V_{Bus} = 800 \text{ V}$ $I_D = 120 \text{ A}$		696		nC
Q_{gs}	Gate-source charge			123		
Q_{gd}	Gate-drain charge			150		
$T_{d(on)}$	Turn-on delay time	$V_{GS} = -5/20 \text{ V}$ $V_{Bus} = 600 \text{ V}$ $I_D = 150 \text{ A}$ $R_{Gon} = 2.7\Omega$; $R_{Goff} = 1.6\Omega$		30		ns
T_r	Rise time			30		
$T_{d(off)}$	Turn-off delay time			50		
T_f	Fall time			25		
E_{on}	Turn on energy	$V_{GS} = -5/20 \text{ V}$ $T_j = 150 \text{ }^\circ\text{C}$		3		mJ
E_{off}	Turn off energy			2		mJ
R_{Gint}	Internal gate resistance			2		Ω
R_{thJC}	Junction-to-case thermal resistance				0.141	$^\circ\text{C}/\text{W}$

Table 4 • Body Diode Ratings and Characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
V_{SD}	Diode forward voltage	$V_{GS} = 0 \text{ V}$; $I_{SD} = 120 \text{ A}$		4		V
		$V_{GS} = -5 \text{ V}$; $I_{SD} = 120 \text{ A}$		4.2		
t_{rr}	Reverse recovery time	$I_{SD} = 120 \text{ A}$; $V_{GS} = -5 \text{ V}$; $V_R = 800 \text{ V}$ $dI/dt = 3000 \text{ A}/\mu\text{s}$		90		ns
Q_{rr}	Reverse recovery charge			1650		nC
I_{rr}	Reverse recovery current			40.5		A

3.2 SiC Schottky Diode Ratings Characteristics (Per SiC Diode)

This section shows the SiC Schottky diode ratings and characteristics of the MSCSM120AM11CT3AG device.

Table 5 • SiC Schottky Diode Ratings and Characteristics

Symbol	Characteristic	Test Conditions		Min	Typ	Max	Unit
V_{RRM}	Peak repetitive reverse voltage					1200	V
I_{RRM}	Reverse leakage current	$V_R = 1200 \text{ V}$	$T_J = 25 \text{ }^\circ\text{C}$	30	600	μA	
			$T_J = 175 \text{ }^\circ\text{C}$		450		
I_F	Forward current		$T_C = 100 \text{ }^\circ\text{C}$		90		A
V_F	Diode forward voltage	$I_F = 90 \text{ A}$	$T_J = 25 \text{ }^\circ\text{C}$		1.5	1.8	V
			$T_J = 175 \text{ }^\circ\text{C}$		2.1		
Q_C	Total capacitive charge	$I_F = 90 \text{ A}$			390		nC
C	Total capacitance	$f = 1 \text{ MHz}, V_R = 400 \text{ V}$			423		pF
		$f = 1 \text{ MHz}, V_R = 800 \text{ V}$			315		
R_{thJC}	Junction-to-case thermal resistance					0.333	°C/W

3.3 Thermal Package Characteristics

This section shows the thermal and package characteristics of the MSCSM120AM11CT3AG device.

Table 6 • Package Characteristics

Symbol	Characteristic	Min	Max	Unit
V_{ISOL}	RMS isolation voltage, any terminal to case $t = 1 \text{ min}, 50/60 \text{ Hz}$	4000		V
T_J	Operating junction temperature range	-40	175	°C
T_{JOP}	Recommended junction temperature under switching conditions	-40	$T_{Jmax} - 25$	°C
T_{STG}	Storage temperature range	-40	125	°C
T_C	Operating case temperature	-40	125	°C
Torque	Mounting torque	To heatsink	M4	2 3 N.m
Wt	Package weight			110 g

Table 7 • Temperature Sensor NTC¹

Symbol	Characteristic	Min	Typ	Max	Unit
R ₂₅	Resistance at 25 °C		50		kΩ
ΔR ₂₅ /R ₂₅			5		%
B _{25/85}	T ₂₅ = 298.15 K		3952		K
ΔB/B		T _C = 100 °C	4		%

$$R_T = \frac{R_{25}}{\exp\left[B_{25/85}\left(\frac{1}{T_{25}} - \frac{1}{T}\right)\right]} \quad T: \text{Thermistor temperature}$$

R_T: Thermistor value at T

Note:

1. See application note APT0406 on www.microsemi.com.

3.4

Typical SiC MOSFET Performance Curves

This section shows the typical performance curves of the MSCSM120AM11CT3AG SiC MOSFET.

Figure 3 • Maximum Thermal Impedance




Figure 4 • Output Characteristics, $T_J = 25^{\circ}\text{C}$




Figure 5 • Output Characteristics, $T_J = 175^{\circ}\text{C}$




Figure 6 • Normalized RDS(on) vs. Temperature




Figure 7 • Transfer Characteristics













Figure 8 • Switching Energy vs. R_g**Figure 9 • Switching Energy vs. Current****Figure 10 • Capacitance vs. Drain Source Voltage****Figure 11 • Gate Charge vs. Gate Source Voltage****Figure 12 • Body Diode Characteristics, T_J = 25 °C****Figure 13 • 3rd Quadrant Characteristics, T_J = 25 °C**

Figure 14 • Body Diode Characteristics, $T_J = 175^\circ\text{C}$ **Figure 15 • 3rd Quadrant Characteristics, $T_J = 175^\circ\text{C}$** **Figure 16 • Operating Frequency vs. Drain Current**

3.5 Typical SiC Diode Performance Curves

This section shows the typical performance curves of the MSCSM120AM11CT3AG SiC diode.

Figure 17 • Maximum Thermal Impedance




Figure 18 • Forward Characteristics






Figure 19 • Capacitance vs. Reverse Voltage



4 Package Specifications

This section shows the package outline of the MSCSM120AM11CT3AG device. All dimensions are in millimeters.

Figure 20 • Package Outline



See application note 1906 – Mounting Instructions for SP3F Power Modules on www.microsemi.com.



Microsemi
2355 W. Chandler Blvd.
Chandler, AZ 85224 USA

Within the USA: +1 (480) 792-7200
Fax: +1 (480) 792-7277

www.microsemi.com © 2020 Microsemi and its corporate affiliates. All rights reserved. Microsemi and the Microsemi logo are trademarks of Microsemi Corporation and its corporate affiliates. All other trademarks and service marks are the property of their respective owners.

Microsemi's product warranty is set forth in Microsemi's Sales Order Terms and Conditions. Information contained in this publication is provided for the sole purpose of designing with and using Microsemi products. Information regarding device applications and the like is provided only for your convenience and may be superseded by updates. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is your responsibility to ensure that your application meets with your specifications. THIS INFORMATION IS PROVIDED "AS IS." MICROSEMI MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION, INCLUDING BUT NOT LIMITED TO ITS CONDITION, QUALITY, PERFORMANCE, NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT WILL MICROSEMI BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL OR CONSEQUENTIAL LOSS, DAMAGE, COST OR EXPENSE WHATSOEVER RELATED TO THIS INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROSEMI HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROSEMI'S TOTAL LIABILITY ON ALL CLAIMS IN RELATED TO THIS INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, YOU PAID DIRECTLY TO MICROSEMI FOR THIS INFORMATION. Use of Microsemi devices in life support, mission-critical equipment or applications, and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend and indemnify Microsemi from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microsemi intellectual property rights unless otherwise stated.

Microsemi Corporation, a subsidiary of Microchip Technology Inc. (Nasdaq: MCHP), and its corporate affiliates are leading providers of smart, connected and secure embedded control solutions. Their easy-to-use development tools and comprehensive product portfolio enable customers to create optimal designs which reduce risk while lowering total system cost and time to market. These solutions serve more than 120,000 customers across the industrial, automotive, consumer, aerospace and defense, communications and computing markets. Headquartered in Chandler, Arizona, the company offers outstanding technical support along with dependable delivery and quality. Learn more at www.microsemi.com.

MSCC-0344-DS-01055-1.0-0120