ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	51-00019.M	Connector, PPL7, 5C, 0° plug, 7x38 mm, chrome, solder, Ø2.2-5.2 mm wire, molding style	2	
2	30-00918	Wire, 4C BC, 24 AWG, UL20280, 300V, 80C, 4.8 mm braided shield, FT2, TPU	1	
3	24-00206	Overmold, PPL7 strian relief, 10x24 mm	2	TPU





Front View
(Not to Scale)



Front View
(Not to Scale)

50-00019.M	Wiring Diagram wire color	50-00019.M
1	Red	1
2	White	2
3	Black	3
4	Yellow	4
5	Drain/Shield	5

Revision:	Date:	Description:
A	3/27/2018	Initial release

Prepared: AG Digitally signed by AG Date: 2018.04.19 15:48:47 -07'00'

Verified: AW Digitally signed by AW Date: 2018.04.19 15:59:24 -07'00'

Dimensions are in millimeters.
Tolerances:
X: ± 0.5 mm
X.X: ± 0.3 mm
X.XX: ± 0.05 mm

Notes:

RoHS compliant

Function test: no open, no short circuit, no intermittent

Description:

Cable, 1830 mm, 5C PPL7 plug 51-00019.M to same, 24 AWG, UL20280 30-00918

TENSILITY

tel 1.541.323.3228 *800* 877.670.7118
fax 1.541.323.4202 *web* tensility.com

Size: A

Part number: 10-02263

Scale: 1:1

Sheet 1 of 1

5 4 3 2 1

To see a custom version of this cable assembly, call Tensility at 541-323-3228 or email engineering@tensility.com