



Main

Range	Spacial
Product name	Spacial S3CM
Application	Human-machine dialogue application
Category	Control enclosure
Enclosure nominal height	11.81 in (300 mm)
Enclosure nominal width	11.81 in (300 mm)
Enclosure nominal depth	7.87 in (200 mm)
Installation accessory type	Suspension system
Product destination	Interface
Device composition	1 body 1 door with lock 2 rail 1 reinforcement plate 1 trim frame

Complementary

Body type	Single piece body
Door type	Solid
Number of doors	Rear 1
Door opening side	Reversible 120 °)
Lock type	3 mm double-bar lock
Mounting plate description	Without mounting plate
Type of gland plate	Without gland plate
Accessibility for operation	Rear
Removable parts	Door by hinges Trim frame by screws 2 rails by screws
Material	Enclosure and front face steel Trim frame aluminium
Surface finish	Epoxy-polyester powder
Color	Enclosure Gray RAL 7035) Front face Gray RAL 7040)
Net Weight	16.41 lb(US) (7.444 kg)

Environment

IP degree of protection	IP54 IEC 60529
IK degree of protection	IK10 IEC 62262

Ordering and shipping details

Category	80033-ENCLOSURE SYSTEMS POLYESTER
Discount Schedule	ES1
GTIN	3606480212949
Nbr. of units in pkg.	1
Package weight(Lbs)	16.41 lb(US) (7.444 kg)

Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	12.60 in (32 cm)
Package 1 width	12.60 in (32 cm)
Package 1 Length	8.66 in (22 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------