



ISO9001:2008 Certified

Mechanical Specifications (mm)

	D:	22.0	± max
	T:	6.0	± max
	Lead Diameter	1.0	± nom
	S:	7.8	± nom
	L:	38.0	± nom
	Coating Lead Run Down (straight Leads)	4.0	± max
	B:	9.20	± nom
	C:	2.74	± nom



Electrical Specifications

	Resistance:	1.0	Ω	± 20 %
	Max Steady State Current upto 65°C:	20.00	A	
	Max Rec. Energy Rating:	65	J	
	Actual Failure Instantaneous Energy:	200	J	
	Maximum Capacitance @ 120 VAC:	4,400	µf	
	Maximum Capacitance @ 240 VAC:	1,000	µf	
	Resistance @ 100% Max Current:	0.00	Ω	
	Resistance @ 50% Max Current:	0.03	Ω	
	Body Temperature at 100% Max Current:	187.00	°c	
	Dissipation Constant:	32.4	mw/°c	
	Thermal Time Constant:	40	Sec.	
	Material Type (for Beta and Curve):	B		

SL22 1R020	
Date: 01/08/2016	Drawn by: Erin Landis
Ametherm, Inc. 961 Fairview Drive Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Chad Terry
	Revision: B