



## REVISION A


DO NOT SCALE FROM THIS PRINT

















EXPLODED VIEW

NOT TO SCALE
(FOR CLARITY ONLY)

## NOTES:

1. MATERIAL:

BODY, OUTER CONTACT, COUPLING NUT & CLAMP NUT: STAINLESS STEEL. PIN & LOCK RING: BERYLLIUM COPPER. SOLDER FERRULE: BRASS. GASKET & O-RING: SILICONE RUBBER. BEAD: ULTEM 1000.

2. FINISH:

BODY, OUTER CONTACT, COUPLING NUT & CLAMP NUT: PASSIVATED. PIN & SOLDER FERRULE: GOLD OVER NICKEL PLATE,
50 µIN MIN GOLD OVER 50 µIN MIN NICKEL.

3. PCI P/N: 3173.

UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE IN INCHES.
TOLERANCES ARE:
DECIMALS ANGLES
XX + 0.110.31 1.°

.XX: ±.01[0.3] 1 ° .XXX: ±.005[0.13] .XXXX: ±.0005[0.013]

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS CONFIDENTIAL AND
PROPRIETARY INFORMATION AND ALL DESIGN,
MANUFACTURING, REPRODUCTION, USE, PATENT RIGHTS
AND DALES RIGHTS, ARE CORRESS, VERSICHED OF SAMPEC,
OF DART, TO ARY UNIAUTHORIZED PERSON OR ENTITY HOR
PERPODULCES, THANSFERRED OR INCORPORATE IN IAWY
OTHER PROJECT IN ARY MANURES WITHOUT THE EXPRESS
MRITTER CONSISTENT OS SAMPEC, INFO

DO NOT SCALE DRAWING

SHEET SCALE: 2.5:1



520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail info@SAMTEC.com code 55322

DESCRIPTION: 2.4MM PLUG, SOLDER CLAMP FOR STORM AT-150 CABLE

DWG. NO. PRF24-P-C-EP-150A-SS

BY: SAMUEL C 08/03/2020 SHEET 1 OF 1

F:\DWG\MISC\MKTG\PRF24-P-C-EP-150A-SS-MKT.SLDDRW