



Sierra Wireless AirLink® Antenna: 2-in-1 Dome

AirLink® Antenna: 2-in-1 Dome

The 2-In-1 low profile MiMo Dome has been tested and certified to operate with AirLink routers and gateways.

The antenna enclosure contains two isolated high performance antenna elements spanning 698-2700MHz MIMO/diversity at LTE frequencies.

The antenna in ground plane independent, and maintains a high level of performance even when mounted on a non-metallic surface.

		Specification	
PART NO.		6001123	
ELECTRICAL DATA	_		
Frequency Rang	Elements 1 & 2	698-960 / 1700-2700MHz	
Operational Bands	Elements 1 & 2	2G/3G/4G LTE	
Peak gain: Isotropic	Elements 1 & 2	698-960MHz	2.3dBi
		1710-2700MHz	5dBi
Isolation*	Elements 1 & 2	> 15dB	
Correlation Co-efficient	•	< 0.1	
Polarisation	•	Vertical	
Impedance	•	50Ω	
Max Input Power	•	25W	
MECHANICAL DATA			
Dimensions	Height	62 mm (2.4")	
	Diameter	176 mm (6.7″)	
Operating Temp		-22°/ 176°F (-30° / +	-80°C)
Material		ASA & Diecast Aluminu	JW
Colour		White	
Ingress Protection		IP66	
Weight		1282g	

MOUNTING DATA		
Mounting Type		Bolt Mount
Mounting hole		19mm (3/4")
CABLE DATA		
Cell / LTE Cables	Туре	CS29
	Length	5m (16ft)
	Termination	SMA Plug

*Measured with 5m (17') of CS29 cable

About Sierra Wireless

Sierra Wireless is building the Internet of Things with intelligent wireless solutions that empower organizations to innovate in the connected world. We offer the industry's most comprehensive portfolio of 2G, 3G, and 4G embedded modules and gateways, seamlessly integrated with our secure cloud and connectivity services. OEMs and enterprises worldwide trust our innovative solutions to get their connected products and services to market faster.

For more information, visit www.sierrawireless.com.

Sierra Wireless, the Sierra Wireless logo, AirLink, and the red wave design are trademarks of Sierra Wireless. Other registered trademarks that appear on this brochure are the property of the respective owners. © 2017 Sierra Wireless, Inc. 2017.05.15

