


## Protect It! 6-Outlet Surge Protector, 4 ft. (1.22 m) Cord, 790 Joules, Diagnostic LED, Light Gray Housing

MODEL NUMBER: TLP604



Safeguard your computer, printer, scanner, router, modem and other small home electronics against dangerous surges, spikes and line noise. Recommended for any desktop, network or home application requiring AC line protection.

### Features

#### 790-Joule Surge Protection for Home or Office Electronics

- Protects your computer, printer, scanner, router, modem and other small home electronics against even the strongest surges and spikes
- Recommended for any desktop, network or home electronics application requiring AC line protection
- Full normal mode (H-N) and common mode (N-G/H-G) line surge suppression
- Filters out disruptive EMI/RFI line noise that can cause equipment damage or data loss
- Exceeds IEEE 587 Category A and B surge suppression specifications

#### 6 Outlets Accept Wide Range of Electronic Devices

- 6 NEMA 5-15R AC outlets accept most computers and peripherals
- Special end outlet designed for bulky transformers without blocking other outlets

#### Premium Safety Features

- Lighted on/off switch provides one-touch control over connected equipment
- Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required
- Diagnostic LED confirms protection status at a glance
- Conforms to current UL 1449 3rd Edition safety standards
- ABS fire retardant plastic case provides extra safety and durability

#### Fits Effortlessly Into Your Workstation

- 4 ft. AC power cord with NEMA 5-15P plug reaches nearby outlets
- Keyhole slots on bottom panel provide convenient wall or desk mounting options

#### Backed by Tripp Lite's Ultimate Lifetime Insurance

- \$20,000 Ultimate Lifetime Insurance covers any connected components damaged by power surge (U.S., Canada and Puerto Rico only)

### Highlights

- 6 NEMA 5-15R outlets—one designed for a bulky transformer
- 790-joule surge protection rating
- Filters out threatening EMI/RFI line noise
- 15A resettable circuit breaker prevents dangerous overloads
- 4 ft. AC power cord with NEMA 5-15P plug

### Package Includes

- TLP604 Protect It! 6-Outlet Surge Protector, Light Gray Housing
- Owner's manual

## Specifications

| <b>OVERVIEW</b>                              |  |
|--|--|
| UPC Code                                     | 037332100498   |
| <b>INPUT</b>                                 |  |
| Nominal Input Voltage(s) Supported           | 120V AC  |
| Recommended Electrical Service               | 120V (110-125V)  |
| Input Cord Gauge Type                        | 14 gauge; SJT  |
| Input Cord Gauge (AWG)                       | 14   |
| Voltage Compatibility (VAC)                  | 120  |
| Maximum Surge Amps                           | 36000  |
| Input Plug Type                              | NEMA 5-15P   |
| Input Cord Details                           | SJT  |
| Input Cord Length (ft.)                      | 4  |
| Right-Angle Plug                             | No   |
| Input Cord Length (m)                        | 1.22   |
| Integrated Cord Clip                         | No   |
| <b>OUTPUT</b>                                |  |
| Frequency Compatibility                      | 50 / 60 Hz   |
| Output Receptacles                           | (6) 5-15R  |
| Circuit Breaker (amps)                       | 15   |
| Transformer Accommodation                    | (2) Yes  |
| Outlet Orientation                           | Single row   |
| Right-Angle Outlets                          | No   |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |  |
| Diagnostic LED(s)                            | Yes  |
| Switches                                     | Combination AC circuit breaker and 2 position on/off power switch            |
| Diagnostic LED Details                       | Built-in LED confirms suppressor "protection present" (green) status         |
| <b>SURGE / NOISE SUPPRESSION</b>             |  |
| AC Suppression Joule Rating                  | 790  |
| AC Suppression Response Time                 | < 1 ns   |
| Protection Modes                             | Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression |
| UL1449 Let Through Rating                    | 500V   |

|   |   |
|---|---|
| EMI / RFI Filtering                               | Yes   |
| Automatic Shut-Off                                | Yes   |
| <b>DATALINE SURGE SUPPRESSION</b>                 |   |
| Cable (Coax) Protection                           | No  |
| Network (Ethernet) Protection                     | No  |
| Telephone/DSL Protection                          | No  |
| <b>PHYSICAL</b>                                   |   |
| Material of Construction                          | Plastic   |
| Power Cord Color                                  | Light Gray  |
| Housing Color                                     | Light Gray  |
| Mounting Holes or Slots                           | Yes   |
| Slot or Hole Mount Measurement (Center to Center) | Distance between slots = 101 mm; Distance between slot height = 28 mm                                     |
| Outlets Measurement (Center to Center)            | 28.5mm  |
| Receptacle Color                                  | Gray  |
| Shipping Dimensions (hwd / in.)                   | 12.60 x 1.60 x 4.90   |
| Shipping Dimensions (hwd / cm)                    | 32.00 x 4.06 x 12.45  |
| Shipping Weight (lbs.)                            | 1.00  |
| Shipping Weight (kg)                              | 0.45  |
| Unit Dimensions (hwd / in.)                       | 10.800 x 1.850 x 1.230  |
| Unit Dimensions (hwd / cm)                        | 27.43 x 4.70 x 3.12   |
| Unit Weight (lbs.)                                | .80   |
| Unit Weight (kg)                                  | 0.36  |
| <b>FEATURES &amp; SPECIFICATIONS</b>              |   |
| Antimicrobial                                     | No  |
| Rotatable Outlets                                 | No  |
| <b>STANDARDS &amp; COMPLIANCE</b>                 |   |
| Product Certifications                            | CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL Listed |
| Product Compliance                                | RoHS  |
| <b>WARRANTY &amp; SUPPORT</b>                     |   |
| Product Warranty Period (Worldwide)               | Lifetime limited warranty   |



1000 Eaton Boulevard  
Cleveland, OH 44122  
United States

|   |  |
|---|--|
| Connected Equipment Insurance<br>(U.S., Canada & Puerto Rico) | \$20,000 <a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime<br>Insurance</a> |
|---|--|



© 2022 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.