

3M

Gripping Material

Plain (fabric)-backed 3M™ Gripping Material

- GM613 (Ultra Soft)
- GM630 (Very Soft)
- GM640 (Soft)
- GM530 (Soft Firm)
- GM110 (Firm)

Preliminary Technical Data & Application Guide

March 2014

Product Description 3M™ Gripping Materials utilizes 3M's proprietary micro-replication technology to create a high-friction surface, which can enhance grip and reduce slippage. The plain-backed versions have a nylon knit backing that provides stretch in the cross-web direction; and would typically be attached to other substrates by sewing. It is ideally suited for applications requiring some stretch, such as work or athletic gloves. 3M™ Gripping Material products are designed to be used alone, or as a two-part mated system. When used alone (on a single surface), the 3M™ Gripping Materials provide a strong secure grip. When used as a two-part mated system, for example, on a glove and handle bar, grip strength is maximized. As firmly as 3M™ Gripping Material holds, it releases just as easily.

Product Construction

Product	Color	Standard Roll Width	Standard Roll Length
3M™ Gripping Material; Plain-backed	Black: GM110, GM530 & GM640; Grey: GM630 & GM613	24 inches (61 cm)	36 yards (32.9 m), 72 yards (65.8 m)

3M™ Gripping Material

Plain (fabric)-backed 3M™ Gripping Material

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Property	3M™ Gripping Material				
	GM613	GM630	GM640	GM530	GM110
Weight - oz/yd ² (g/m ²)	12.4 (420)	12.4 (420)	12.4 (420)	11.6 (394)	10.9 (370)
Thickness - mils (mm)	39 (0.99)	39 (0.99)	39 (0.99)	37 (0.94)	32 (0.81)
Gripping Polymer Hardness (Shore A) ASTM D2240	13	30	40	59	73
Coefficient of Friction (COF): ASTM D1894 Grip to Grip System ¹ – Dry / Wet Grip to Synthetic Classic Leather ² – Dry / Wet	2.3 / 2.1 2.1 / 1.4	2.2 / 1.7 1.9 / 1.3	2.0 / 1.7 1.5 / 1.1	2.4 / 1.7 1.3 / 1.2	2.4 / 1.5 1.4 / 1.1
Abrasion Resistance: ASTM D3389 (H18, 500g load) Wear through – revolutions Wear rate – mg/revolution	500 0.53	1200 0.34	2500 0.19	5000 0.10	>10,000 0.02
Tensile Strength: ASTM D5035 - lbf/inch (N/cm)	MD* CD* 47.1 (82.5) 33.9 (59.4)	48.1 (84.3) 25.6 (44.9)	49.4 (86.4) 31.2 (54.6)	55.0 (96.4) 35.4 (62.0)	58.0 (101.6) 33.8 (59.1)
Elongation at Break: Modified ASTM D882 - % Elongation	MD* CD* 118 199	81 158	86 192	93 189	85 224
Tear Resistance: ASTM D5734 - lb (N)	MD* CD* – –	1.4 (6.3) –	1.4 (6.4) –	1.2 (5.6) –	1.7 (7.8) –
Stiffness – Flexural Rigidity: ASTM D1388 - μjoule/m	MD* CD* 6.6 3.6	13.7 6.3	47.3 22.2	52.7 28.2	67.3 27.9

¹COF of 3M™ Gripping Material to itself.

²Synthetic Nassimi Classic Faux Leather (Vinyl)

*MD: machine direction, *CD: cross direction.

Features

- Composed of tough, durable thermoplastic urethane (GM110 and GM530) or thermoplastic elastomer (GM640, GM630 and GM613) **Note:** GM640, GM630 and GM613 contain mineral oil which can migrate out of the product under some conditions
- The 3M™ Gripping Materials contain 3,000 stems or ‘tiny fingers’ per square inch to provide excellent grip performance in both wet and dry conditions
- Stems can provide a cushioned feel for many applications
- Good abrasion resistance
- Durable nylon fabric backing
- Wide useable temperature range: -40°F to 140°F (-40°C to 60°C)
(Dependent upon the particular application)

3M™ Gripping Material

Plain (fabric)-backed 3M™ Gripping Material

Application Ideas If needed, the 3M™ Gripping Material can be bonded in place prior to sewing to prevent it from moving during the sewing process. 3M™ 6035PC or 6038PC Pressure Sensitive Adhesives work well for this purpose. Consult the Technical Data Sheets for these products for additional information.

Please Note: Use of adhesive may make it slightly harder to sew due to the adhesive sticking to the needle. When possible, place adhesive in areas where it will not come in contact with the sewing needle.

Application Techniques Provided below are the recommended sewing conditions for the plain-backed 3M™ Gripping Materials:

Sewing Machine Foot: Use a walking leather type foot

Needle Size & Type: The needle used will be dependant on the type of material the 3M™ Gripping Material will be attached to. Some needle types that have been successfully used in the past include a DP-11 needle with a round tip and a special left angle pointed tip needle.

Thread: Bulked continuous filament nylon 6 for the needle thread and looper thread.

The 3M™ Gripping Materials should be attached to the body fabric prior to other sewing operations. Attach using a “half pique” seam with a stitch length of 9 to 11 stitches per inch sewn using a double row of stitches with a double type needle to maintain a row distance of 1.5mm.

It is important that the entire surface of the 3M™ Gripping Material be in contact with the substrate. Minimum tension should be used to avoid stretching and distortion of the product.

Converting The plain-backed 3M™ Gripping Material products can be shear cut, die-cut, or converted by other applicable methods, and can be sewn to a wide variety of substrates using most commercially available equipment. Excessive thread tension may cause tearing or cutting of the material. Minimum tension should be used to avoid stretching and distortion of the product. Avoid direct contact with heated processing surfaces, in excess of 160°F (71°C), for prolonged periods of time.

Care & Maintenance Can be hand washed with mild detergent in cool to warm water. Surface contamination, such as lint or other debris, can be easily removed with Scotch® Tape, Scotch® Lint Roller, Scotch® Lint Sheets, or other lint removing mechanisms.

Important: Test each application following the appropriate care instructions required for the finished product. The actual life of the 3M™ Gripping Material depends on the cleaning method and wear conditions.

- Do not iron
- Do not bleach
- Do not use in a dryer
- Do not dry clean

3M™ Gripping Material

Plain (fabric)-backed 3M™ Gripping Material

Storage Store under normal conditions of 60° to 80°F (16° to 27°C) and 40% to 60% Relative Humidity in the original carton.

Shelf Life To obtain best performance, use this product within 18 months from date of manufacture.

Technical Information The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.



Industrial Adhesives and Tapes Division

3M Center, Building 225-3S-06
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (Fax)
www.3M.com/Gripping



Recycled Paper
40% pre-consumer
10% post-consumer

3M is a trademark of 3M Company.

Printed in U.S.A.
©3M 2014 (3/14)