


EVB Series

75-120 W

Tri-Mode Dimming™ (0-10 V & TRIAC/ELV) Constant Current LED Drivers with Fast Startup Time

| Input Voltage | Max. Output Power | Output Voltage | Output Current | Efficiency | Max. Case Temperature | THD | Power Factor | Dimming Method | Dimming Range | Startup Time | |
|---------------------------|-------------------------|-------------------|-------------------|----------------------|---------------------------------------|-------|-----------------|--|-------------------------|-----------------|--|
| 120 to 277 Vac nominal | 120 W | 30-42 V | 1.8-2.3 A CC | up to 87% typical | 90°C (measured at the hot spot) | < 20% | > 0.9 | Forward-Phase, Reverse-Phase & 0 - 10V | 1 - 100% (% of lout) | 400 ms | |

CC: Constant Current



| ERP Part Number | Nominal Input Voltage | lout (mA) | Max Output Power | Output Voltage Range (Vdc) | | | | | |
|----------------------|-----------------------------|--------------|------------------------|-------------------------------------|-----|--|--|--|--|
| | (Vac) | | (W) | Min | Max | | | | |
| EVB080W: up to 80 W | | | | | | | | | |
| EVB080W-1800S-42 | 120 - 277 | 1800 | 75.6 | 30 | 42 | | | | |
| EVB100W: 91 to 100 W | | | | | | | | | |
| EVB100W-2300S-40 | 120 - 277 | 2300 | 92 | 30 | 40 | | | | |

Notes: 1. Not Class 2



APPLICATIONS

- Street Lights
- Industrial LED Lighting
- Troffers
- Outdoor LED Lighting

FEATURES

- Compatible with TRIAC (forward-phase or leading-edge), ELV (reverse-phase or trailing-edge) and 0-10 V dimmers
- TRIAC and ELV dimming only at 120 Vac
- Outdoor surge protection: 3 kV line to line/6 kV line to earth
- Linear 0-10V dimming transfer function: 10V=100%, 1V=10%, 0.1V=194
- · Can also be offered with two and three channels
- Protections: output open load, over-current and short-circuit (hiccup), and over-temperature with auto recovery
- Conducted and radiated EMI: Compliant with FCC CFR Title 47 Part 15 Class B (120 Vac)/Class A (277 Vac) and EN55015 (CISPR 15) at 220/230/240 Vac
- Complies with ENERGY STAR® luminaire specification and DLC (DesignLight Consortium®) technical requirements
- · IP66-rated case with silicone-based potting
- Lifetime: 50,000 hours min at 70°C case temperature
- 90°C maximum case hot spot temperature
- Class 2 power supply (some models only)





CHINA Operations

tel: +86-756-6266298 No. 8 Pingdong Road 2 Zhuhai, Guangdong, China 519060

www.erp-power.com

SaveEnergy@erp-power.com

USA Headquarters tel: +1-805-517-1300

893 Patriot Drive, Suite E Moorpark, CA 93021, USA