



D <u>LEAD FREE REFLOW PROFILE</u> 10 SEC. MAX.



TOTAL TIME ABOVE 220°C IS 60 SECONDS MAX.



	PART NUMBER	SML-LXF0805SUGC-TR	REV.	О
Ī	DATE	E.C.N. NUMBER AND REVISION COMMENTS		REV.
	3.14.03	E.C.N. #10967.		Α
	07.09.04	E.C.N. #11148.		В
	09.03.04	E.C.N. #11165.		O
	2.14.05	E.C.N. #11148.		О

	ELECTRO-OPTICAL CH	CTRO-OPTICAL CHARACTERISTICS TA = 25°C				
	PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
	PEAK WAVELENGTH		574		nm	
	FORWARD VOLTAGE		2.2	2.6	v_f	
	REVERSE VOLTAGE	5.0			Vr	I _r =100uA
С	AXIAL INTENSITY		70		mcd	I _f =20mA
	VIEWING ANGLE		120		2x theta	
	EMITTED COLOR:	GREEN				
	FPOXY LENS FINISH:	WATER (CLEAR LENS			

LIMITS OF SAFE OPERATION AT 25°C		
PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	160	mA
STEADY CURRENT	25	mA
POWER DISSIPATION	100	mW
DERATE FROM 25°C	-1.2	mW/*C
OPERATING TEMP.	-40 TO +85	*C
STORAGE TEMP.	-40 TO +85	•C
* t<10uS		

NOTES:

- THE POLARITY MARK IS ORIENTED TOWARDS THE TAPE SPROCKET HOLE.
- B 2. LEAD FREE.

CAUTION: MOISTURE SENSITIVE DEVICE
PER JEDEC LEVEL 4 STANDARDS

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION UNCONTROLLED DOCUMENT



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 FAX: +1.847.359.6538 WEB: WWW.LUMEX.COM 2.0mm x 1.25mm SURFACE MOUNT LED, 574nm SUPER ULTRA GREEN LED, WATER CLEAR LENS, TAPE AND REEL D

THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC., EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHA KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL, AND SHALL PROFECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

REEL.	DATE:	01.12	.01	DRAWN BY:	BC	
	PAGE:	1 OF	1	CHKD BY:	-	
I ALL	SCALE:	N/A		APRVD BY:	-	
1ALL	UNIT: mm [INCH]		Po			