

## Housing - HC-D 50-TFQ-76/O1STM32G - 1645215

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)




HEAVYCON sleeve housing D50, for double locking latch, height 76 mm, without support 1x M32, straight conductor exit

The illustration shows the version  
HC-D 50-TFQ-76/O1STM32G



### Key commercial data

|                                      |   |
|--------------------------------------|---|
| Packing unit                         | 1 PCE   |
| GTIN                                 | <br>4 017918 913137 |
| Weight per Piece (excluding packing) | 273.53 GRM  |
| Custom tariff number                 | 85389099  |
| Country of origin                    | Germany   |

### Technical data

#### Dimensions

|        |       |
|--------|-------|
| Height | 76 mm |
| Width  | 56 mm |
| Length | 82 mm |

#### Ambient conditions

|                                      |                   |
|--------------------------------------|-------------------|
| Degree of protection of housing (IP) | IP65              |
| Ambient temperature (operation)      | -40 °C ... 125 °C |

#### General

|              |                                     |
|--------------|-------------------------------------|
| Note         | For contact inserts HC-D25, A16/A32 |
| Design       | D50                                 |
| Housing type | Sleeve housings                     |
| Locking type | For double locking latch            |

# Housing - HC-D 50-TFQ-76/O1STM32G - 1645215

## Technical data

### General

|                              |                     |
|------------------------------|---------------------|
| No. of cable exits           | 1                   |
| Cable exit                   | Straight            |
| Screw connection             | None                |
| Type of the screw connection | 1x M32              |
| Housing material             | Aluminum die-cast   |
| Housing surface material     | Powder-coated, gray |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27140816 |
| eCl@ss 4.1 | 27140816 |
| eCl@ss 5.0 | 27143424 |
| eCl@ss 5.1 | 27143424 |
| eCl@ss 6.0 | 27143424 |
| eCl@ss 7.0 | 27440209 |
| eCl@ss 8.0 | 27440209 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000437 |
| ETIM 3.0 | EC000437 |
| ETIM 4.0 | EC000437 |
| ETIM 5.0 | EC000437 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 31261502 |
| UNSPSC 7.0901 | 31261502 |
| UNSPSC 11     | 31261502 |
| UNSPSC 12.01  | 31261502 |
| UNSPSC 13.2   | 31261502 |

## Accessories

### Accessories

Full screw connection

## Housing - HC-D 50-TFQ-76/O1STM32G - 1645215

### Accessories

Cable gland - HC-K-KV-M32(15-21) - 1690642



Plastic screw connection up to 5 bar, thread length: 10 mm, cable diameter: 15 - 21 mm, WAF 36, screw connection: M32

Cable gland - HC-M-KV-M32(14-21) - 1690587



Metal screw connection up to 5 bar, thread length: 8 mm, cable diameter: 14 - 21 mm, WAF 34, screw connection: M32

Cable gland - HC-M-KV-M32(19-27) - 1646010



Metal screw connection up to 5 bar, thread length: 8 mm, cable diameter: 19 - 27 mm, WAF 43, screw connection: M32

### Drawings

Dimensioned drawing

