

FRACTION: ±1/64 ANGLE: ±2°

UNLESS OTHERWISE SPECIFIED

THERMALLY PROTECTED, PER UL E92971, CSA 48508

I/WE CERTIFY THAT SAMPLES OF THIS MOTOR HAVE BEEN FULLY TESTED BY THE UNDERSIGNED AND THAT ALL SPECIFICATIONS HAVE BEEN REVIEWED FOR PRODUCTION. MULTIPRODUCTS COMPANY, INC. IS NOT RESPONSIBLE FOR MOTORS THAT FAIL IN THE FIELD DUE TO INSUFFICIENT TESTING OF THE SAMPLE MOTORS. I/WE AGREE TO PROVIDE MULTIPRODUCTS COMPANY. INC. WITH CURRENT DRAWINGS AND IN-HOUSE TEST PROCEDURES AS THEY BECOME AVAILABLE. ANY CHANGES THAT I/WE MAY MAKE WHICH OCCUR AFTER THE DATE SHOWN ARE SUBJECT TO REVIEW AND MAY AFFECT UNIT PRICE AND/OR DELIVERY DATES.

SIGNATURE PRINT NAME IN ORDER TO BEGIN PRODUCTION, MULTIPRODUCTS COMPANY, INC. MUST HAVE SIGNED APPROVAL.

NO LOAD SPEED: 3.2 RPM NO LOAD CURRENT: 0.70 A

STALL TORQUE: 180 IN-LB STALL CURRENT: 0.88 A



PART NAME/DESCRIPTION:		MULTIPRODUCTS		
DRAWN BY: DAB	DATE:	10/12/2016	SCALE: 0.75:1	MATERIAL: -

DATE: 10/12/2016 | PART NUMBER: CHK'D BY: DMR MOD-UL52-9903A APPR'D BY: RP DATE: 10/12/2016