

APPLICATOR PARTS LIST

SIDEWISE PIN RECEIPT

**AMP INCORPORATED
HARRISBURG, PENNA.**

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.
1	WIRE CRIMPER	1	4539323	42	SHEAR PLATE-LEFT	1	811855-1
2	INS. CRIMPER	1	2465264-2	43	SHEAR BLOCK RIGHT	1	386372
3	ANVIL	1	811225-4	44	FLOATING SHEAR	1	465406
4	ANVIL SPACER	1	810070-5	45	RETAINING PLATE FAT	1	811714-3
5	SHEAR BLADE			46	RETAINING PLATE REAR	1	386370
6	REAR SHEAR PLATE			47	SPRING SHEAR RETURN	1	374322
7	SPACER REAR ANVIL	1	452621-1	48	SHEAR DEPRESSOR	1	811101-2
8	FRONT SHEAR PLATE			49	KEY SHEAR RET.	1	386358
9	REAR ANVIL SPACER PLT.			50	GUARD MOUNT	1	811306-1
10	FRONT ANVIL SPACER PLT.			51	HOLDER, PUNCH	1	810498-3
11	TOOL SPACER	1	4704937	52	PUNCH ASSY	1	210738-1
12	CRIMP SPACER	1	375548	53			
13	FRONT STRIP GUIDE	1	810971-1	54	REAR STRIP GUIDE BODY	1	811527-3
14	REAR STRIP GUIDE	1	465440-4	55			
15	RAM	1	471912	56			
16	TOOL HOLDER			57			
17	ADJ. CRIMP MOUNT			58			
18	ADJ. BLOCK	1	811102-1	59			
19	APPLICATOR MOUNT ASSY.			60	SCREW, SOC. HD. CAP	3	811651-3
20	BASE PLATE	1	465100	61			
21	BASE BLOCK	1	465101	62			
22	STRIP GUIDE PLATE	1	465414-1	63			
23	ANVIL HOLDER			64	1" AIR FEED ASSY.	1	690021
24	WIRE STOP GUIDE	1	811787-1	65	TENSION ADJ. PLATE	1	374999
25	STRIPPER - WIRE STOP	1	386361-1		MISCELLANEOUS		
26	STRIPPER MOUNT	1	386362	66			
27	RETAINER PLATE	1	389078	67	LUBRICATOR ASSY	1	465184-2
28	STRIPPER MOUNT BRACKET	1	387715-1	68	OIL, SYNTHETIC	1	22014-1
29	STRIPPER BUSHING	1	389049-1	69			
30	STOCK DRAG	1	386955	70			
31	STOCK DRAG HANDLE			71			
32	STOCK DRAG STUD	1	374900	72			
33	STOCK DRAG SPRING	1	370572				
34	STOCK DRAG ADJ. NUT	1	21022-3				
35	FEED FINGER HOLDER	1	386942				
36	FEED FINGER	1	386941				
37	FEED FINGER TIP	1	387251				
38	FEED FINGER GUIDE	1	689915-2				
39	BASE CASTING	1	570238				
40	GUARD	1	460881-1				
41	BRACKET GUARD	1	811304-1				

CRIMPING DATA		TERMINALS
TO APPLY TERMINAL		GROUP I
CRIMP HEIGHT		010 X .055
WIRE SIZE	GROUP I	GROUP II
	60354	60354
28	.025	
26	.027	.026
24		.029
22		.032
CRIMP	SIZE	TYPE
WIRE	.055	F
INSUL.	.070	O
SLEEVED		FEED
INSULATION RANGE		WIRE RANGE
.035 - .042		28 - 26 60354
.035 - .065		26 - 22 60354
EXPLODED VIEW		GROUP II
A-6002-10 A-6002-13		010 X .135
		60804
REMARKS:		
⚠ USE WITH ITEM 2215		

**— INACTIVE —
FOR REPLACEMENT ONLY**

<input type="checkbox"/> DENOTES WEARING PARTS <input type="checkbox"/> RECOMMEND PURCHASE REPLACEMENT	
THIS APPLICATOR IS TO BE USED ON AMP-O-ELECTRIC 1-471273-2 AIR FEED	
SERIAL NO.	DATE SHIPPED
CUSTOMER NAME AND ADDRESS	DESIGNER
APPLICATOR NUMBER	APP'D.
REV. R 565739-1	SHEET 1 OF 1

REV.	REVISION RECORD	DATE	BY	ECN
L	REDDAWN W/CHANGES	1-4-73	RS	6-907
M	ITEM 45 WAS -2, ADD ITEM 60804	5-24-73	RS	6-9634
M	REV. PER ECN	7-23-73	RS	6-9908
P	REV. PER ECN	8-21-75	RS	6-1013
R	REV. PER ECN	5-19-76	RS	6-1016
R	INACTIVE FOR	2-24-77	RS	6-1016

FOR HARDWARE
SEE 687511-2