

**RIDERSERIES
SRC-I 1CO**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Relay base for the RIDERSERIES RCI relays

- 1 and 2 CO contacts
- Screw and PUSH IN connection
- Standard and low heights

General ordering data

Order No.	8869470000
Type	SRC-I 1CO
Version	RIDERSERIES, Relay base, Continuous current: 16 A ⁽¹⁾ , 12 A, Screw connection
GTIN (EAN)	4032248614424
Qty.	10 pc(s).

**RIDERSERIES
SRC-I 1CO**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Ratings

Conductor connection system	Screw connection	Humidity	40 °C / 93 % rel. humidity, no condensation
Weight	36 g	Wire cross-section, solid, max.	2.5 mm ²

Dimensions and weights

Width	16 mm	Height	77 mm
Depth	62 mm	Weight	36 g
Net weight	36 g		

Temperatures

Operating temperature	-40 °C...+70 °C	Storage temperature	-40 °C...+70 °C
-----------------------	-----------------	---------------------	-----------------

Connection data

Clamping range, rated connection	1.5 mm ²	Clamping range, rated connection, min.	0.5 mm ²
Clamping range, rated connection, max.	2.5 mm ²	Tightening torque, min.	0.5 Nm
Tightening torque, max.	0.7 Nm	Stripping length, rated connection	8 mm

Output

Rated switching voltage	240 V AC	Max. switching voltage, AC	400 V
Continuous current	16 A ⁽¹⁾ , 12 A		

Insulation coordination

Rated voltage	250 V	Clearance and creepage distances for control side - load side	≥ 8 mm
Dielectric strength for control side - load side	5 kV _{eff} / 1min	Protection degree	IP 20
Insulating material group	IIIa	Pollution severity	2
Surge voltage category	III		

Further details of approvals / standards

Standards	IEC 61810-1, UL508
-----------	--------------------

Classifications

ETIM 3.0	EC001456	UNSPSC	30-21-19-17
eClass 5.1	27-37-16-03	eClass 6.0	27-37-16-03
eClass 7.0	27-37-16-03		

Approvals

Approvals



**RIDERSERIES
SRC-I 1CO**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Downloads

Declaration of Conformity [K295_12_10.pdf](#)