



Performance:

- a. Insertion Loss: <0.3dB
- b. Return Loss: >20dB.
- c. Fiber Extension: -100nm<H<+100nm.
- d. Ferrule End-Face Radius: 10<R<25mm(ST).
- e. Apex Offset: ≤50um.
- f. Increase in insertion Loss after 500 mating: 0.2dB Max.
- g. Operation Temperature: -40°C to +70°C.
- h. Storage Temperature: -40°C to +80°C.

WSW P/N	Length (M)
DK-2611-01	1
① DK-2611-02	2
DK-2611-03	3
DK-2611-05	5
DK-2611-07	7
DK-2611-10	10

⑤	3.0mm ST/PC MM Connector/ Silver	4
④	ST 3.0mm Boot/ Black	2
③	ST 3.0mm Boot/ Red	2
②	Heatshrink Tube/ Black	2
①	Ø3.0mm OM1 62.5/125 Duplex Cable/ LSZH/ Orange	1
No.	Specifications	Qty

RoHS compliant
Unit: mm

Scale	Free				Date	Name	Customer-No.
TOLERANCE					Drawn	Fred	
					Approved	Segal	ASSMANN WSW-No. DK-2611-xx
DIM	TOL	①	Add P/N, dimensions, update the tolerance and drawing No.	03.12.2018	Segal	Drawing-No. ① ASS 8435 CA rev01	
		②	Drawn	08.30.2017	Fred	Replace Sheet	
Angle	TOL	Id.	Modification	Date	Name		

