RoHS 2011/65/EU REACH compliant Conflict minerals free

GEYER quartz technology

Clock Oscillator SMD-version +3,3V

model	KXO-V94T
frequency	20,0 MHz
frequency stability at -40° ~ +85°C	± 50 ppm
operating temperature	-40° ~ +85°C
storage temperature	-55° ~ +100°C
symmetry	45% ~ 55% at 50% V_{DD} level
rise & fall time max.	5 ns (10% V_{DD} ~ 90% V_{DD} level)
"O" level max.	VOL: 10% V_{DD}
"1" level min.	VOH: 90% V_{DD}
input voltage V_{DD}	+3,3V DC ±5%
tri-state control voltage (Pin#1)	VIH: V_{DD} x 0,7 min. VIL: V_{DD} x 0,3 max.
supply voltage	-0,5V ~ +4,0V
input current max.	7,0mA
output load max.	15pF (CMOS)
start up time max.	10 ms
disable delay time max.	150 ns
enable delay time max.	10 ms
stand by current max.	10 µA (Pin #1=VIL)
contents of reel	1000 pcs. / 3000 pcs.
part no.	12.90322

Dimensions (mm):



Suggested soldering pad:



Reflow soldering condition:



Test circuit:



Output waveform:



Tape specification:



reel diameter 245 mm

GEYER ELECTRONIC e.K. Lochhamer Schlag 5 82166 Gräfelfing/München
Tel. +49 89 546868-0 quartz@geyer-electronic.de www.geyer-electronic.de