AMP CT

TE Internal #: 1-292250-2

PCB Mount Header, Right Angle, Wire-to-Board, 12 Position, 2 mm [.079 in] Centerline, Partially Shrouded, Tin, Through Hole - Solder,

AMP CT

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles > CT 2mm Post Header Assembly Box H Kink



Connector System: Wire-to-Board

Number of Positions: 12

Number of Rows: 1

Centerline (Pitch): 2 mm [.079 in] PCB Mount Orientation: Right Angle

All CT 2mm Post Header Assembly Box H Kink (51)

PCB Contact Termination Area Plating Material Thickness

Features

Product Type Features	
Connector System	Wire-to-Board
Header Type	Partially Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
PCB Connector Assembly Type	PCB Mount Header
Configuration Features	
Number of Positions	12
Number of Rows	1
PCB Mount Orientation	Right Angle
Electrical Characteristics	
Operating Voltage	125 VAC
Body Features	
Primary Product Color	Natural
Contact Features	
Contact Mating Area Length	4.2 mm[.165 in]

1 μm[39.37 μin]



Contact Layout	Inline
Mating Pin Diameter	.6 mm[.024 in]
Contact Shape & Form	Round
Contact Mating Area Plating Material Finish	Bright
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Brass
Contact Mating Area Plating Material	Tin
Contact Type	Pin
Contact Current Rating (Max)	4 A
Termination Features	
Round Termination Post & Tail Diameter	.6 mm[.024 in]
Termination Post & Tail Length	3.2 mm[.126 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Mating Alignment Type	Polarization
Mating Retention	Without
PCB Mount Retention Type	Kinked Legs
Mating Retention Type	Detent Window
Connector Mounting Type	Board Mount
Mating Alignment	With
PCB Mount Alignment	Without
PCB Mount Retention	With
Housing Features	
Housing Material	Nylon 66
Centerline (Pitch)	2 mm[.079 in]
Dimensions	
Connector Length	25.8 mm[1.016 in]
Connector Height	8.8 mm[.346 in]
Connector Width	5.8 mm[.228 in]
PCB Thickness (Recommended)	.8 mm[.031 – .063 in]
Usage Conditions	
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]



Operation/Application

Assembly Process Feature	Pick and Place Cover
Circuit Application	Power & Signal
Industry Standards	
Agency/Standard	CSA, UL
Approved Standards	CSA LR7189, UL E28476
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	200

Bag, Box

Product Compliance

Packaging Type

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # CAT-AM7017-C7671
Common Termination Contacts —
POWER TRIPLE LOCK



TE Part # CAT-AM7017-H8172

AMP COMMON TERMINATION


HOUSINGS



Also in the Series | AMP CT



PCB Connector Mounting(46)



PCB Headers & Receptacles(756)



Wire-to-Board Connector Assemblies & Housings(256)



Wire-to-Board Connector Contacts(8)

Customers Also Bought



TE Part #292206-2 MINI COMMON TERMINATION HEADERS



TE Part #3-292208-0 MINI CT D/R DIP 30P V NAT



TE Part #2-292208-8 MINI CT D/R DIP 28P V NAT



TE Part #3-292208-6 MINI CT D/R DIP 36P V NAT



TE Part #2-292208-6 MINI CT D/R DIP 26P V NAT



TE Part #2-292208-4 MINI CT D/R DIP 24P V NAT

Documents

Product Drawings
CT P/HDR BOX H ASSY 12P W/KINK

English

CAD Files

3D PDF

3D



Customer View Model

ENG_CVM_CVM_1-292250-2_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-292250-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-292250-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Product Specifications

Product Specification

English

AMP COMMON TERMINATION (CT), CONNECTOR, 2mm PITCH, M/T TYPE, LEAD FREE VERSION

Japanese

Product Specification

Japanese

Product Environmental Compliance

TE Material Declaration

English