Wire Rope Cutter

95

Compact size, lightweight, high performance level High transmission joint design makes cutting 20% easier Box joint design for greater stability

- > for cutting high-strength wire ropes up to up to 5/32" (4 mm) and cable 3/16" (6 mm)
- > at just 6 1/4" (160 mm) length this tool is considerably more powerful than many larger wire rope cutters
- > included thumb lock and opening spring
- > ball bearing steel for a long service life
- > induction hardened cutting edges
- > cuts cleanly and evenly without wire ends splaying or fanning out





Product Number	Packaging	→ Inch mm		Head	Handles	Ø Inch Ø mm	Ø Inch Ø mm	۵ ^۲ ۵ Ibs
95 62 160	Х	<mark>6 1/4</mark> 160	🛠 🛯 🖾 🖼 🗰	polished	multi-component grips	<mark>3/16</mark> 6.0	<mark>5/32</mark> 4.0	0.38

Cable Cutters for Wire Rope and ACSR

95


- > for ACSR, wire ropes, steel rods, copper and aluminum cables
- > suitable for cutting overhead cables with strain relief wire
- > angular cutting blades prevent fanning out
- > optimum transmission ratio for high cutting performance
- > bolted cutter head, replaceable
- > lightweight
- > cutter head: high-grade special tool steel, multi stage oil-hardened
- > handles: aluminum, high-strength

95 81 600

With reinforced cutter head for higher performance, also cuts piano wire







							Cutting capacities				
Product Number	Packaging	←→ Inch mm		Head	Handles	mm ²	Ø Inch Ø mm	● <mark>Ø Inch</mark> Ø mm	Ø Inch Ø mm	AWG	۵ <mark>۲</mark> ۵ Ibs
95 71 445		17 1/2 445	♦◎∎∎	polished	plastic grips	95	25/64 10	9/32 7	-	3/0	2.39
95 71 600		23 5/8 600	♦◎∎∎	polished	plastic grips	150	35/64 14	23/64 9	-	5/0	3.84
95 77 600		23 5/8 600	<u> </u>	polished	plastic dipped insulated, VDE-tested	150	35/64 14	23/64 9	-	5/0	5.02
95 81 600		23 5/8 600	♦⊚∎∎	polished	plastic grips	150	<mark>5/8</mark> 16	<mark>25/64</mark> 10	11/64 4.5	5/0	4.97
95 79 445	Spare cutter head for 95 71 445										
95 79 600	- Spare cutter head for 95 71 600 / 95 77 600										
95 89 600	Spare cutter head for 95 81 600										