

# P/N 97-AQ132D 132-Pin Amp Footprint PQFP-to-PGA Socket

#### **FEATURES**

- Convert surface-mount PQFP packages to an Amp interstitial PGA footprint.
- Reduce costs by using less-expensive PQFP packages to replace PGA footprints in existing designs.
- Pins are mechanically fastened and soldered to board using Aries patented process, creating a reliable electrical connection and rugged contact.
- Consult factory for Panelized Form or for mounting of consigned chips.
- RoHS version available, see Ordering Information

#### **GENERAL SPECIFICATIONS**

- BODY MATERIAL: Tg170 FR-4, 0.062 [1.58] thick, with 1-oz. Cu traces
- PADS: bare Cu protected with ENIG (Immersion Au over Electroless Ni) to eliminate coplanarity concerns and solder bridges associated with hot air solder leveling
- PINS: Brass 360 1/2-hard per UNS C36000, ASTM B16/B16M
- PIN PLATING: Sn/Pb 93/7 per ASTM B579-73 over 100μ [2.54μ] Ni per SAE AMS-QQ-N-290 -or -

 $10\mu$  [0.254 $\mu$ ] Au per MIL-G-45204 over  $100\mu$  [2.54 $\mu$ ] Ni per SAE AMS-QQ-N-290 for RC version


• OPERATING TEMPERATURE: 221°F [105°C]

### **MOUNTING CONSIDERATIONS**

- SUGGESTED PCB HOLE SIZE:  $0.028 \pm 0.003$  [0.71  $\pm 0.08$ ] dia.
- Will plug into existing PGA footprint with matching Pad assignments

ALL DIMENSIONS: INCHES [MILLIMETERS]


ALL TOLERANCES:  $\pm 0.005$  [0.13] UNLESS OTHERWISE SPECIFIED ROW-TO-ROW AND PIN-TO-PIN  $\pm 0.003$  [ $\pm 0.08$ ] NON-CUMULATIVE CONSULT FACTORY FOR OTHER SIZES AND CONFIGURATIONS




**CUSTOMIZATION:** In addition to the standard products shown on this page, Aries specializes in custom design and production. Special materials, platings, sizes, and configurations can be furnished, depending on the quantity. **NOTE:** Aries reserves the right to change product general specifications without notice.

## **ORDERING INFORMATION**

Specify...
P/N 97-AQ132D or
P/N 97-AQ132D-P for Panelized form
P/N 97-AQ132D-RC or
P/N 97-AQ132D-RC-P, for RoHS Panelized form







Bristol, PA 19007-6810 USA
TEL (215) 781-9956 • FAX (215) 781-9845
WWW.ARIESELEC.COM • INFO@ARIESELEC.COM