

Specification Sheet

Part Number: 151-01311



Bundling clip allows bundle to be parallel, perpendicular or offset from the panel and mounting hole for routing versatility.

Compact I-beam design provides a robust solution for all bundles, small to large.

Used in conjunction with HellermannTyton's 4x oval push pins, bundling clip prevents rotation of the bundle.

Oval hole can also be used as a portable hole joining two routings together.

Bundling Clip, 90 Deg with 6.5x12.5 Oval Hole, 40mm Long, PA66HIRHSUV, Black, 4000/ctn

Article Number 151-01311

Type TC90OVAL

Color Black (BK)

Quantity Per carton

Product Description HellermannTyton's bundling clips allow a harness to be routed around a corner and attached to the panel at this location.

Short Description Bundling Clip, 90 Deg with 6.5x12.5 Oval Hole, 40mm Long, PA66HIRHSUV, Black, 4000/ctn

Global Part Name TC90OVAL-PA66HIRHSUV-BK

| | |
|---|--|
| Length L (Imperial) | 1.47 |
| Length L (Metric) | 37.3 |
| Fixation Method | Bolt |
| Width W (Imperial) | 0.59 |
| Width W (Metric) | 15.0 |
| Height H (Imperial) | 1.66 |
| Height H (Metric) | 40.8 |
| Mounting Hole Diameter D (Imperial) | 0.27 x 0.51 |
| Mounting Hole Diameter D (Metric) | 6.5 x 12.5 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.27 |
| Mounting Hole Diameter D Max (Imperial) | 0.51 |
| Mounting Hole Diameter D Max (Metric) | 12.5 |
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut | PA66HIRHSUV |

| | |
|------------------------------|-----------------------------------|
| Flammability | UL 94 HB |
| Halogen Free | Yes |
| UV Resistant (Yes/No) | Yes |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 4000 |
| Package Quantity (Metric) | 4000 |
| Customs Number | 3926909988 |

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)