

Data sheet | Item number: 770-693

Lockout cap; 3-pole; for cutouts; Plastic; white

www.wago.com/770-693



Color:

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Item description

Cover *WINSTA*® MIDI 3-pole

Realize the electrical installation easily and quickly: The cover from the *WINSTA*® MIDI product line is the solution for quick, straightforward installation. An extensive range of accessories complements the *WINSTA*® product line from WAGO. The *WINSTA*® MIDI Pluggable Connection System with Push-in CAGE CLAMP® spring pressure connection technology facilitates safe electrification. Due to the built-in test slot, it is possible to check connections even when they are plugged in. That saves time and reduces installation labor and costs.

Push-in CAGE CLAMP® spring pressure connection technology – pluggable installation instead of laborious screw connections!

WINSTA® is the pluggable connection system that is perfectly tailored to the strict requirements of electrical installation. It offers fast, secure and, above all, error-free installation of components and cables. Enjoy the benefits of the pluggable version of our maintenance-free spring pressure connection technology too! Plan your installation with *WINSTA*® MIDI accessories from WAGO.

-
- pre-assembled versions
- convenient installation and commissioning

Data

Connection data

Connection 1

Pole number	3
-------------	---

Mechanical Data

Mounting type	Snap-in flange
---------------	----------------

Suitable	for cutout
----------	------------

Material Data

Note (material data)	Information on material specifications can be found here
----------------------	--

Color	white
-------	-------

Subject to changes. Please also observe the further product documentation!



Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.051 MJ
Weight	1.7 g

Environmental requirements

Processing temperature	-5 ... +40 °C
Continuous operating temperature	-35 ... +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data

Product Group	20 (Winsta)
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 8.0	EC002863
ETIM 7.0	EC002863
PU (SPU)	100 pcs
Packaging type	box
Country of origin	DE
GTIN	4017332755450
Customs tariff number	39269097900

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Documentation

Bid Text

770-693 X81 - Datei	2019 年2月19日	xml 2.7 kB	Download
770-693 doc - Datei	2015 年1月13日	doc 23.6 kB	Download

Subject to changes. Please also observe the further product documentation!



CAD/CAE-Data

CAD data

2D/3D Models 770-693	URL	Download
----------------------	---------------------	--------------------------

CAE data

WSCAD Universe 770-693	URL	Download
------------------------	---------------------	--------------------------

ZUKEN Portal 770-693	URL	Download
----------------------	---------------------	--------------------------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 770-693	URL	Download
--	---------------------	--------------------------

Lockout cap; 3-pole; for cutouts; Plastic; white

Installation Notes

Product family

WINSTA® MIDI

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!