

# Thermal Grease 21-420

Version TDS.21-420.V.B.0

### Description

Thermal Grease 21-420 is grease-like thermal interface material, designed to perform low thermal resistance between high watt density chips like CPUs, GPUs, ASICs, Northbridge chipsets and heat sink. It provides outstanding reliability while remaining stable through all industry standard reliability testing.



### Benefits

- Moderate Viscosity
- Solvent-free
- Non-Curing Material (No Need For Curing Oven)
- RoHS Compliant


### Applications

- CPUs (Notebooks, PCs, Servers)
- LED Solid State Lighting
- GPUs
- Northbridge Chipsets
- ASICS Chips


### Typical Properties

Properties	21-420	Test Method
Thermal	Thermal Conductivity (W/m-K)	2
	Thermal Resistance @20 psi (in <sup>2</sup> °C/W)	0.029
	Thermal Resistance @40 psi (in <sup>2</sup> °C/W)	0.027
	Continuous Use Temp. (°C)	-40~150
Physical	Substrate	Silicone
	Color	Grey
	Viscosity (cP)	Customized (<150,000)
	Specific Gravity (g/cc)	2.2
Electrical	Volume Resistivity (ohm-cm)	>10 <sup>11</sup>
Regulatory	Flammability Rating	V0
	Shelf Life @25°C (Months)	6
	RoHS Compliant	YES

Thermal Resistance vs Compression



### Ordering Information



### Standard Package

- 21-420-001-030M = thermal grease 21-420 30cc tube (80g)
- 21-420-001-600M = thermal grease 21-420 600cc can (1kg)
- 21-420-001-001L = thermal grease 21-420 1L can (2kg)
- 21-420-001-001G = thermal grease 21-420 1 Gallon can (8kg)

### Storage Requirement

Room Temperature Between 8 to 28 degree  
R.H. 50%  
\* Unopened Original Package

### Disclaimers

- The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the issuing date of this TDS. When using our products, no matter what type of equipment they might be used for, be sure to make a written agreement on the specifications with us in advance. The design and specifications in this TDS are subject to change without prior notice.
- Do not use the products beyond the specifications described in this TDS. This TDS explains the typical performance of the products as individual component. Before use, check and evaluate their operations when installed in your products.
- Install the following systems for a failsafe design to ensure safety if these products are to be used in equipment where a defect in these products may cause the loss of human life or other significant damage, such as damage to vehicles (automobile, train, vessel), traffic lights, medical equipment, aerospace equipment, electric heating appliances, combustion/gas equipment, rotating equipment, and disaster/crime prevention equipment.

JONES TECH PLC  
3 Dong Huan Zhong Road, BDA, Beijing 100176 China  
TEL: +86 10 6786 2636 FAX: +86 10 67860291  
E-mail: sales@jones-corp.com

