



FEMALE

A04	A05	A08	D04	B05

NOTE:

MATERIAL

M12 INSULATOR PA66, UL94V-0, BLACK
 CONTACT GOLD FLASH PLATED BRASS
 NUT & SHELL NICKEL PLATED BRASS

ELECTRICAL

RATED CURRENT 2A(8P) / 4A(4/5P)
 VOLTAGE 30V(8P) / 60V(5P) / 250V(4P)
 INSULATOR RESISTANCE 100 MOhms MIN.
 CONTACT RESISTANCE 10 mOhms MAX.
 MATING CYCLES 100 CYCLES MIN

ENVIRONMENT

OPERATION TEMPERATURE -40°C TO +85°C
 IP RATING IP67

RECOMMENDED TORQUE

0.4Nm TO 0.8Nm

858FYYY-203RCS1

SERIES 858F = M12 FIELD INSTALLABLE
 CONTACT ARRANGEMENT A04 = 4P A-CODE
 A05 = 5P A-CODE
 A08 = 8P A-CODE
 D04 = 4P D-CODE
 B05 = 5P B-CODE
 GENDER 2 = FEMALE
 CABLE OD C = 4mm-8mm OD
 CONTACT PLATING 1 = GOLD FLASH

RoHS COMPLIANT

UNITS = mm

DO NOT SCALE FROM DRAWING



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:

J. KADEL

DATE:

02/04/2022

NorComp

SCALE: NTS

SHEET 1 OF 1

REV 0

DWG NO.

858FYYY-203RCS1