
ALLIGATOR CLIPS

STANDARD .080" (2.03mm) TIP SOCKET TO STANDARD ALLIGATOR CLIP



Construction: Insulator is molded PVC. Alligator jaws are nickel-plated steel. .080" socket is machined brass nickel plated. Contact spring is silver plated beryllium copper.

Colors: Available in 10 colors.

STANDARD .080" (2.03mm) TIP SOCKET TO MINIATURE ALLIGATOR CLIP

Part No.	Description	
8015	.080" Tip Skt on Miniature	1.219"
	Alligator Clip	.080" DIA. SOCKET 40" DP


.40" DP.

Construction: Insulator is molded PVC. Alligator jaws are nickel-plated steel.
.080" socket is machined brass nickel plated. Contact spring is silver plated beryllium copper.

Colors: Available in all 10 colors.

STANDARD ALLIGATOR CLIP SOLDERLESS ASSEMBLY WITH INSULATION SLEEVE


Part No.	Description
9288	Standard
	Alligator
	Solderless
	Assembly



Construction: Nickel-plated steel. Insulation sleeve is molded tenite acetate. **Colors:** Available in red and black.

FULLY INSULATED LARGE ALLIGATOR WITH FINGER FLANGES TO BANANA SOCKET, ACCEPTS SHROUDED BANANA PLUGS

Part No.	Description	
9468	Large	4
	Alligator Clip	
	to Banana	226"
	Socket,	
	Accepts Std.	┵┢
	or Shrouded	
	Plugs	-



Construction: Insulator is molded nylon. Alligator jaws and banana socket are formed steel nickel plated. (IEC 1010 compliant)

Colors: Available in 10 colors.

FULLY INSULATED LARGE ALLIGATOR WITH FINGER FLANGES TO BANANA SOCKET, ACCEPTS SHROUDED BANANA PLUGS

Part No. 9432	Description Small Fully Insulated Alligator Clip	3.30"
	to Ban. Skt, Accepts Shrd. or Standard Banana Plugs	.65"163" DIA. BANANA SOCKET

Construction: Insulator is molded nylon. Alligator jaws and banana socket are formed steel nickel plated. IEC 1010 rating: 1000 Volts Cat III, 30 amps. **Colors:** Black, red, green, blue, yellow, white.

FEMALE 8-32 THREAD TO STANDARD ALLIGATOR CLIP


Part No.	Description	
8047	Standard	
	Alligator to Female 8-32 Thread	4 1.69" → 1.6

Construction: Insulator is molded PVC. Alligator jaws and 8-32 female thread are nickel-plated steel.

Colors: Available in 10 colors.

FEMALE 6-32 THREAD TO MINIATURE ALLIGATOR CLIP


Part No.	Description
8040	Miniature
	Alligator to
	Female 6-32
	Thread



Construction: Insulator is molded PVC. Alligator jaws and 8-32 female thread are nickel-plated steel.

Colors: Available in all 10 colors.


STANDARD BANANA SOCKET TO MINIATURE ALLIGATOR CLIP



Construction: Insulator (banana socket only) is molded nylon. Alligator jaws are nickel-plated steel. Banana socket is a nickel plated brass.


Colors: Available in all 10 colors.

1000 VOLT INSULATED ALLIGATOR CLIP, ACCEPTS SHROUDED BANANA PLUGS



Construction: Insulator is molded nylon. Alligator jaws and banana socket are formed steel nickel plated. IEC 1010 rating: 1000 Volts Cat III, 30 amps. **Colors**: Black, red, green, blue, yellow, white.

SMALL FULLY INSULATED ALLIGATOR CLIP, ACCEPTS SHROUDED



Construction: Insulator is molded nylon. Alligator jaws and banana socket are formed steel nickel plated. IEC 1010 rating: 1000 Volts Cat III, 30 amps. **Colors**: Black, red, green, blue, yellow, white.