



- NOTES
1. ONE EXAMPLE OF THE ROTATION OF REF. NO.7, 8 AND REF. NO.1 IS SHOWN.
 2. THE RECOMMENDED CLAMP TORQUE REF. NO.8 : 3 TO 4 N · m.
LOCTITE 243, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF. NO. 8 FROM LOOSENING.
 3. THE RECOMMENDED CLAMP TORQUE REF. NO.11 : 0.2 TO 0.3 N · m.
LOCTITE 243, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF. NO. 11 FROM LOOSENING.
 4. THIS PRODUCT TO BE USED WITH CABLECLAMP, JR13WC-*(T2). THE RECOMMENDED CLAMP TORQUE : 3 TO 4 N · m, AND LOCTITE 243, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT FROM LOOSENING. * DESIGNATE DIAMETER OF APPLICABLE CABLE.
 5. THE CABLE PULL AND TWISTING STRENGTH AND OTHER CHARACTERISTICS MAY DIFFER, DEPENDING ON THE CABLE STRUCTURE. PLEASE CONFIRM BEFORE THE USE.

6	PHOSPHOR BRONZE	NICKEL PLATING	11	STAINLESS STEEL	JISPH177 HE80M SOCKET SET SCREW M2.6X0.45
5	STEEL	NICKEL PLATING	10	ACRYLONITRILE BUTADIENE RUBBER (BLACK)	
4	BRASS	NICKEL PLATING	9	PHOSPHOR BRONZE	NICKEL PLATING
3	ACRYLONITRILE BUTADIENE RUBBER (BLACK)		8	BRASS	NICKEL PLATING
2	POLYBUTYLENE TEREPHTHALATE (BLACK) UL94V-0		7	BRASS	NICKEL PLATING
1	ZINC ALLOY	NICKEL PLATING			

NO.	MATERIAL	FINISH	REMARKS	NO.	MATERIAL	FINISH	REMARKS
6	PHOSPHOR BRONZE	NICKEL PLATING		11	STAINLESS STEEL		
5	STEEL	NICKEL PLATING		10	ACRYLONITRILE BUTADIENE RUBBER (BLACK)		
4	BRASS	NICKEL PLATING		9	PHOSPHOR BRONZE	NICKEL PLATING	
3	ACRYLONITRILE BUTADIENE RUBBER (BLACK)			8	BRASS	NICKEL PLATING	
2	POLYBUTYLENE TEREPHTHALATE (BLACK) UL94V-0			7	BRASS	NICKEL PLATING	
1	ZINC ALLOY	NICKEL PLATING					

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1					

<p>HIROSE ELECTRIC CO., LTD.</p>	<p>Approved : HY. KOBAYASHI Checked : HY. KOBAYASHI Designed : HY. KISHI Drawn : MK. INOUE</p>	<p>18.02.22 18.02.22 18.02.21 18.02.06</p>	<p>DRAWING NO. PART NO. CODE NO.</p>	<p>EDC-116688-31-00 HR22-12WTL P-20PCC(31) CL122-0064-9-31</p>
----------------------------------	--	--	--	--

FORM HCO011-5-7