## ATGBICS ST-ST OM4, Fibre Optic Cable, Multimode, Duplex, Aqua, 30m

**Brand :** ATGBICS **Product code:** CAB-OM4-ST-ST-30M-D

**Product name:** ST-ST OM4, ATGBICS Fibre Optic Cable,

Multimode, Duplex, Aqua, 30m

ST-ST OM4, ATGBICS Fibre Optic Cable, Multimode, Duplex, Aqua, 30m

ATGBICS ST-ST OM4, Fibre Optic Cable, Multimode, Duplex, Aqua, 30m:

This product is high quality ST-ST (male to male) Fibre Patch Cable. The OM4 cable type has a higher attenuation that helps reduce losses over greater distances. It supports 10 Gigabit Ethernet at lengths measuring up to 550 meters, with 40 Gigabit and 100 Gigabit Ethernet measuring up to 150 meters. depending on the type of transceiver and wavelength. The OM4 cable has a core size of 50 microns and the diameter of the outer cladding is 125 microns.

ATGBICS ST-ST OM4, Fibre Optic Cable, Multimode, Duplex, Aqua, 30m. Cable length: 30 m, Cable type: OFNR, Fibre optic type: OM4, Connector 1: ST, Connector 2: ST, Core diameter: 50  $\mu$ m, Full duplex





| Features   |                      | Features   |   |
|--|----------------------|--|---|
| Cable length * Connector 1 *   | 30 m<br>ST           | Ethernet interface type  | 10 Gigabit Ethernet, 40 Gigabit<br>Ethernet, 100 Gigabit Ethernet |
| Connector 2 * ST  Connector 1 gender * Male  Connector 2 gender * Male  Connector polish type  Cable type * OFNR  Fibre optic type * OM4  Product colour * Aqua colour  Full duplex  Core diameter 50 µm | Male<br>Male         | Insertion loss Return loss Jacket material * Country of origin | 0.2 dB<br>50 dB<br>Polyvinyl chloride (PVC)<br>China              |
|  | OFNR                 | Technical details  Sustainability certificates                 | RoHS  |
|  | 1                    | Doesn't contain  Operational conditions                        | Halogen   |
| Cladding diameter Fiber mode structure   | 125 µm<br>Multi-mode | Operating temperature (T-T)<br>Storage temperature (T-T)       | -40 - 70 °C<br>-40 - 70 °C  |
| Wavelengths supported  | 850,1300 nm          | Weight & dimensions  Cable diameter                            | 2 mm  |
|  |                      | Packaging data   |   |
|  |                      | Quantity per pack  | 1 pc(s)   |



5056468736529

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.