

Specification Sheet

Part Number: TELS-SPK2

Spacers provide distance between two bundles.

Continuous strap and separate heads allow for any bundle diameter, eliminating waste.

Smooth strap prevents cable damage.

UV resistant materials contain an inhibitor which prolongs the life of the tie in outdoor environments.



Extended-Length Tie Spacer, PP, Black, 50/pkg

Article Number 111-32000

Type EL-TY (TELS-SPK2)

Color Black (BK)

Quantity Per bag

Product Description Extended Length Ties provide a high tensile strength strapping system consisting of a continuous strap and separate locking head making it suitable for any bundle diameter, eliminating waste. The smooth strap and specially designed heads with stainless steel pawls provide a strong grip on cables and wires without damage during vibration or in extreme environments. Spacers are available for dual bundle applications.

Short Description Extended-Length Tie Spacer, PP, Black, 50/pkg

Global Part Name EL-TY (TELS-SPK2)-PP-BK

Contents of pkg/kit 50 Spacer

Minimum Tensile Strength (Imperial) 250.0

Minimum Tensile Strength (Metric) 1115.0

Length L (Imperial) 1.2

Length L (Metric) 30.5

Fixation Method 2 piece

Identification Plate Position none

Releasable Closure No

Tie Closure steel pawl

Variant Extended Length

Width W (Imperial) 2.1

Width W (Metric) 53.3

Height H (Imperial) 0.67

Height H (Metric) 17.0

Cable Tie Width Max (Metric) 12.7

Material	Polypropylene (PP)
Material Shortcut	PP
Material Head	Polyacetal, UV stabilized (POMUV) with stainless steel pawl (SS)
Flammability	UL 94 HB
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +239°F (-40°C to +115°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)