

4

3

2

1

© 2021 TE Connectivity. All Rights Reserved.

REVISIONS				
P	LTR	DESCRIPTION	DATE	APVD
A		RELEASED TO PRODUCTION	08DEC2021	LN RL

1 COPPER ALLOY C97.

2 1.27µm MIN GOLD PER ASTM B488 OVER 2.54µm MIN NICKEL PER QQ-N-290 ON ENTIRE STOCK.

3 TWO POSSIBLE LOCATIONS FOR THE LETTER "A" MARKING. OPTIONAL ALTERNATE MARKING: LETTER "S"

4 YELLOW COLOR BAND.

5. APPLICABLE WIRE SIZE: 12-16 AWG  
 WIRE INSULATION DIAMETER: 3.4mm MAX  
 INSULATION STRIP LENGTH: 5.75mm-6.25mm

6. APPLICATION TOOLING:  
 CRIMPING TOOL: TYCO PART NUMBER 601967-1 (M22520/1-01)  
 POSITIONER: TYCO PART NUMBER 601967-2 (M22520/1-02)  
 SELECTOR POSITION: AWG 12 : 8  
                           AWG 14 : 7  
                           AWG 16 : 6  
 CONTACT INSERTION/EXTRACTION TOOL: 1738327-1 (M81969/28-02) OR 1-1192028-1 (M81969/14-04)

7. THIS PRODUCT IS SOLD BY TYCO ELECTRONICS UNDER A LICENSE FROM RADIALL SA.

1738017-1  
 PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN BW	28FEB2005	<b>STE</b> TE Connectivity	
		CHK JPM	28FEB2005		
DIMENSIONS: mm		APVD JPM	28FEB2005	NAME PIN CONTACT, SIZE 12, GPR	
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± 1 PLC ± 2 PLC ±0.05 3 PLC ± 4 PLC ± ANGLES ± FINISH		PRODUCT SPEC	-	SIZE	A200779
MATERIAL		APPLICATION SPEC	-	CAGE CODE	C-1738017
1		WEIGHT	-	DRAWING NO	1738017
2		CUSTOMER DRAWING	SCALE 20:1	SHEET	1 OF 1
				REV	A

1471-9 (3/13)