


JKL PART NUMBER	LENGTH A +/- 2mm	COLOR 5200° KELVIN	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF8300-20A	300mm	LCD HIGH OUTPUT WHITE	1200	390	5 ± 1	4,000	20,000

\* NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			<b>METRIC</b>  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		<b>JKL COMPONENTS CORPORATION</b>					
					TITLE <b>DUAL LEAD LOW PROFILE TIP TYPE HIGH          OUTPUT WHITE MINIATURE FLUORESCENT</b>							
			DRAWN BY <b>L. WENGSTROM</b>		APP'VD BY DATE <b>J.K. 8/12/03</b>		SIZE <b>A</b>	FSCM NO. <b>55335</b>	DRAWING NO. <b>BF8300-20A</b>			
RELEASED <b>8/12/03</b>			APP'VD DATE		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE <b>NONE</b>	RELEASED DATE <b>8/12/03</b>	REVISION DATE	REV. NO.	SHEET <b>1 of 1</b>	
REV. NO.	DESCRIPTION/ECO NUMBER		APP'VD DATE									